

Serie | 2
Classixx
Chimney extractor hood
DWW09W450B Brushed steel


Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 410 m³/h ensures this hood will have your kitchen odour free in no time.
- Halogen lighting provides energy efficient and bright lighting of the hob area.

Technical Data

| | |
|--|--------------------|
| Color chimney : | Stainless steel |
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length electrical supply cord (cm) : | 130 |
| Height of the chimney (mm) : | 553-730/573-730 |
| Height of product, without chimney (mm) : | 246 |
| Minimum distance above an electric hob : | 550 |
| Minimum distance above a gas hob : | 650 |
| Net weight (kg) : | 10.048 |
| Type of control : | mechanical |
| Number of speed settings : | 3 |
| Maximum output air extraction (m ³ /h) : | 410 |
| Maximum output recirculating air (m ³ /h) : | 230 |
| Number of lights : | 2 |
| Noise level (dB(A) re 1 pW) : | 67 |
| Diameter of air outlet (mm) : | 150 / 120 |
| Grease filter material : | Washable aluminium |
| EAN code : | 4242002714165 |
| Connection Rating (W) : | 155 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 60; 50 |
| Plug type : | GB plug |
| Installation typology : | Wall-mounted |

Optional accessories

- DHZ1224 : Chimney extension 500 mm
- DHZ1234 : Chimney extension 750 mm
- DHZ5275 : Recirculating kit
- DHZ5276 : Active carbon filter
- DHZ9551 : Brushed steel back panel



Serie | 2 Hoods

Classixx

Chimney extractor hood DWW09W450B Brushed steel

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Design

- 90 cm wide
- Designed for wall mounted installation
- Height adjustable chimney sections
- Brushed steel canopy and chimney section

Features

- Rocker switch control for extractor speeds and light
- 3 power levels
- 2 x 40W Light
- 3 metal grease filter cassettes

Performance/technical information

- Suitable for ducted or recirculating operation
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 67 dB (A) re 1pW (53 dB (A) re 20 µPa sound pressure)
- Extractor hose 120mm