


IQ500, Gas hob, 90 cm, Stainless steel EC9A5SB90



Optional accessories

HZ211310	Simmer cap
HZ233540	Wok ring
HZ241110	Small pot support
HZ298105	Simmer plate

The gas hob with stepFlame Technology for precise flame control in nine steps.

- ✓ stepFlame Technology – Precise flame control with nine different settings.
- ✓ Dual Wok Burner 5 kW – Go from simmer to stir-fry on one burner.
- ✓ High-quality materials and workmanship – continuous cast-iron pan supports.
- ✓ Biomethane ready – Power your gas hob with renewable biomethane gas.
- ✓ The extremely convenient sword knob makes it easy to control and monitor the power level selected.

Features

Technical Data

Product name/family: gas hob w integrated controls
 Built-in / Free-standing: Built-in
 Energy input: Gas
 Number of cooking zones: 5
 Type of control setting devices:sword knobs
 Min. required niche size for installation (HxWxD):45 x 850-852 x 490-502 mm
 Width of the appliance: 915 mm
 Dimensions: 53 x 915 x 520 mm
 Dimensions of the packed product (HxWxD): . 165 x 1116 x 659 mm
 Weight: 17.3 kg
 Gross weight: 19.5 kg
 Residual heat indicator:without
 Location of control panel: Front
 Basic surface material:Stainless steel
 Color of surface: Stainless steel
 Length electrical supply cord: 150.0 cm
 EAN code:4242003742259
 Gas connection rating: 12500 W
 Fuse protection:3 A
 Nominal power:220-240 V
 Frequency:60; 50 Hz



IQ500, Gas hob, 90 cm, Stainless steel EC9A5SB90

Features

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- Step Flame technology - 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner gas hob including
- Including 1 Dual control wok burner: use an extra wide power range, separately controlling two flame rings.
- Left: Wok burner up to 5 KW (depending on gas type)
- Center front: Economy burner up to 1.75 KW (depending on gas type)
- Center rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 915 x 520
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 - 502)
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 12.5 KW

IQ500, Gas hob, 90 cm, Stainless steel
EC9A5SB90

Dimensioned drawings

