



**iQ500, canopy cooker hood, 70 cm,
Stainless steel
LB78574GB**

**C**

The powerful canopy cooker hood is concealed in a unit above the hob.

✓ LED lights: for optimal visibility and ambience while cooking.

Features

Technical Data

Typology : Built-in/Built-under
Length electrical supply cord : 150 cm
Min. required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm mm
Minimum distance above an electric hob : 500 mm
Minimum distance above a gas hob : 650 mm
Net weight : 9.0 kg
Type of control : Electronic
Maximum output air extraction : 630 m³/h
Boost position output recirculating : 664 m³/h
Maximum output recirculating air : 571 m³/h
Boost position air extraction : 730 m³/h
Number of lights : 2
Noise level : 66 dB(A) re 1 pW
Diameter of air outlet : 120 / 150 mm
Grease filter material : Washable aluminium
EAN code : 4242003686263
Connection Rating : 277 W
Fuse protection : 3 A
Voltage : 220-240 V
Frequency : 50 Hz
Plug type : GB plug
Installation typology : Built-in

Optional accessories

LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)





iQ500, canopy cooker hood, 70 cm, Stainless steel LB78574GB

Features

Design

- 70 cm wide
- Stainless Steel
- White electronic display
- Electronic control via Soft touch button control
- For installation in a kitchen cabinet
- Designed for suspended or flush ceiling installation

Key Information

- Soft touch button control for extractor speeds and light
- 2 x 1W LED lights
- 2 x metal grease filter cassettes
- Steel filter cover, Steel filter cover
- Rim ventilation

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 630 m³/h
 - Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 66 dB(A) re 1 pW
 - Intensive: 69 dB(A) re 1 pW
- 3 x power levels plus intensive setting
- Power rating: 277 W
- Automatic intensive revert
- Noise max. Normal Level: 66 dB*
- Extractor hose 120 mm
- Dimensions (WxD): 700 x 300 mm
- Built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Average Energy Consumption: 104.2 kWh/year*
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*

* In accordance with the EU-Regulation No 65/2014



**iQ500, canopy cooker hood, 70 cm,
Stainless steel
LB78574GB**

Dimensioned drawings

