

**iQ700, canopy cooker hood, 70 cm,  
clear glass black printed  
LB79585GB**

A



The powerful canopy cooker hood is concealed in a unit above the hob.

- ✓ The 775 m<sup>3</sup>/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 51 dB the hood is extremely quiet when being used.

#### Features

##### Technical Data

Typology : Traditional  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 150  
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm  
 Minimum distance above an electric hob : 500  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 9.214  
 Type of control : Electronic  
 Maximum output air extraction (m<sup>3</sup>/h) : 575  
 Boost position output recirculating (m<sup>3</sup>/h) : 370.0  
 Boost position air extraction (m<sup>3</sup>/h) : 775  
 Number of lights : 2  
 Noise level (dB(A) re 1 pW) : 65  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable aluminium  
 EAN code : 4242003688328  
 Connection Rating (W) : 272  
 Current (A) : 3  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50  
 Plug type : GB plug  
 Installation typology : Built-in

#### Optional accessories

LZ75956	Remote control
LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)
LZ46830	CleanAir Recirculation Kit
LZ46810	CleanAir active carbon filter
LZ10ITP00	Long Life odor filter (replacement)



**iQ700, canopy cooker hood, 70 cm,  
clear glass black printed  
LB79585GB**

## Features

### Design

- 70 cm wide
- Stainless Steel
- White electronic display
- Electronic control via Soft touch button control
- Black glass canopy
- For installation in a kitchen cabinet
- Designed for suspended or flush ceiling installation

### Key Information

- Soft touch button control for extractor speeds and light
- 2 x 1W LED lights
- softLight with dimmer function
- 2 x metal grease filter cassettes
- Grease filter saturation indicator
- Glass filter cover, Steel filter cover
- Interval operation
- Rim ventilation

### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 575 m³/h
  - Intensive 775 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 65 dB(A) re 1 pW (51 dB(A) re 20 µPa sound pressure)
  - Intensive: 72 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
- 3 x power levels plus intensive setting
- 
- 
- Automatic intensive revert
- 30 minutes
- Noise max. Normal Level: 65 dB\*
- Extractor hose 120 mm
- Dimensions (WxD): 700 x 300 mm
- built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Average Energy Consumption: 46.6 kWh/year\*
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*

\* In accordance with the EU-Regulation No 65/2014