

iQ700, wall-mounted cooker hood, 33 cm, Black LC37IVV60B



Extractor hood in cube design with high extraction rate for a powerful performance.

- ✓ Brushless motor: powerful and quiet extraction of steam.
- ✓ cookConnect System: Control your extractor hood directly from your Cooktop (with matching cooktop).
- ✓ The climateControl Sensor monitors steam and odours and adjusts the power level automatically.
- ✓ Home Connect: Remote access to a selection of features of your extractor hood via smartphone or tablet. (only in countries where Home Connect service is available).
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of product, without chimney (mm) : 501
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 14.152
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Boost position output recirculating (m3/h) : 400.0
 Number of lights : 2
 Grease filter material : Washable aluminium
 EAN code : 4242003760857
 Connection Rating (W) : 146
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation typology : Wall-mounted

Optional accessories

LZ56200 CleanAir active carbon filter spare part
 LZ00XXP00 Long Life odor filter (replacement)



iQ700, wall-mounted cooker hood, 33 cm, Black LC37IVV60B

Features

Key performance features:

- Max. extraction rate: 400 m³/h
- Noise max. Normal Level: 67 dB*

Features

- climateControl sensor
- Boost function
- cookConnect hob based hood control
- (with Wi-Fi enabled hob)
- Home Connect: Remote Monitoring and Control (only in countries where Home Connect service is available)
- 3 power levels and 2 intensive settings
- softLight with dimmer function
- 2 x 3W LED
- Colour Temperature: 3500 K
- Efficient BLDC motor
- Twin channel high performance fan motor
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- 1 x metal grease filter cassette
- Grease and charcoal filter saturation indicators
- For wall mounted installation

Design

- Black

Cube design

- Chimney hood
- Touch control for extractor speeds and light
- Electronic control

Performance/technical information

- Suitable for recirculated extraction
- Easy installation system
- Max. extraction rate: 400 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 330 m³/h
- Intensive: 400 m³/h
- Noise max. Normal Level: 67 dB*
- Noise levels in recirculation mode:
- Max. normal use: 67 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Intensive: 72 dB(A) re 1 pW (59 dB(A) re 20 µPa sound pressure)
-
-
- Light Intensity: 680 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Dimensions recirculating, chimney (HxWxD): 501-501 x 330 x 291 mm
- Dimensions recirculating, chimneyless (HxWxD): 501 mm x 330 x 291 mm

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014