

iQ100
Chimney hood
LC64BA521B stainless steel



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

✓ The 460 m³/h extraction rate supplies clean air when cooking.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-894/582-1004
 Height of product, without chimney (mm) : 60
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 11.488
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction (m³/h) : 460
 Maximum output recirculating air (m³/h) : 300
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 64
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003606964
 Connection Rating (W) : 160
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation typology : Wall-mounted



Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53251	Active carbon filter
LZ53250	Recirculating kit
LZ50661	Backboard 60 x 72 cm
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm

iQ100
Chimney hood
LC64BA521B stainless steel

Features

Design

- 60 cm wide
- Rocker switch control for extractor speeds and light
- For wall mounted installation

Key features

- 2 x 28W Light
- 2 x metal grease filter cassettes
- Steel filter cover
- 3 x power levels

Performance/technical information

- Suitable for ducted and re-circulating operation
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 64 dB (A) re 1pW (50 dB (A) re 20 µPa sound pressure)