

**iQ100**  
**Glass hood**  
**LC64GB522B stainless steel**



D



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

✓ The 450 m<sup>3</sup>/h extraction rate supplies clean air when cooking.

#### Features

##### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 581-897/581-1007  
 Height of product, without chimney (mm) : 57  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 17.031  
 Type of control : mechanical  
 Number of speed settings : 3  
 Maximum output air extraction (m<sup>3</sup>/h) : 450  
 Maximum output recirculating air (m<sup>3</sup>/h) : 290  
 Number of lights : 2  
 Noise level (dB(A) re 1 pW) : 62  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable aluminium  
 EAN code : 4242003651247  
 Connection Rating (W) : 170  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GB plug  
 Installation typology : Wall-mounted



4 242003 651247

#### Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53251	Active carbon filter
LZ53250	Recirculating kit
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ00XXP00	CleanAir act.carbon filter regenerative

**iQ100**  
**Glass hood**  
**LC64GB522B stainless steel**

#### Features

##### Design

- 60 cm wide
- Rocker switch control for extractor speeds and light
- Stainless steel hood with glass canopy
- Height adjustable chimney sections
- For wall mounted installation

##### Key features

- 2 x high volt halogen spot G9 20W
- 1 x metal grease filter cassette
- Steel filter cover

##### Performance/technical information

- Suitable for ducted and re-circulating operation
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 62 dB (A) re 1pW (48 dB (A) re 20 µPa sound pressure)
- 3 x power levels
- Adjustable automatic after running

##### Optional accessory

- Re-circulating kit - LZ53250