

iQ300
iQ 300
Chimney hood
LC67WA532B stainless steel



A+



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 690 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-864/582-974
 Height of product, without chimney (mm) : 90
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 14.924
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 430
 Boost position output recirculating (m³/h) : 360
 Maximum output recirculating air (m³/h) : 300
 Boost position air extraction (m³/h) : 680
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 58
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable aluminium
 EAN code : 4242003651278
 Connection Rating (W) : 136
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation typology : Wall-mounted

Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53251	Active carbon filter
LZ53250	Recirculating kit
LZ50661	Backboard 60 x 72 cm
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ00XP00	CleanAir act.carbon filter regenerative



4 242003 651278

iQ300
iQ 300
Chimney hood
LC67WA532B stainless steel

Features

Design

- 60 cm wide
- Soft touch button control for extractor speeds and light
- Slimline canopy design
- Height adjustable chimney sections
- For wall mounted installation
- 60 cm Chimney hood

Key features

- Electronic control
- LED lights
- 2 x metal grease filter cassettes
- Steel filter cover
- Removable filter box
- Soft touch button control with illuminated buttons

Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 440 m³/h
 - Intensive 690 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 μ Pa sound pressure)
- 3 x power levels plus intensive setting
- Automatic intensive revert
- Adjustable automatic after running