

iQ700, wall-mounted cooker hood, 60 cm LC68BA572B



A+



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 760 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 46 dB the hood is extremely quiet when being used.

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 15.429
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 430
 Boost position output recirculating (m³/h) : 380.0
 Boost position air extraction (m³/h) : 760
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 60
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 EAN code : 4242003675335
 Connection Rating (W) : 166
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation typology : Wall-mounted

Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53251	Standard odor filter (replacement)
LZ53250	Standard recirculation kit
LZ50660	Backboard 60 x 65 cm
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ00XXP00	Long Life odor filter (replacement)



iQ700, wall-mounted cooker hood, 60 cm

LC68BA572B

Features

Design

- 60 cm wide
- Stainless Steel
- White electronic display
- Electronic control via touchControl
- For wall mounted installation
- Designed for suspended or flush ceiling installation

Key Information

- touchControl for extractor speeds and light
- Boost function
- 2 x LED lights
- softLight with dimmer function
- 2 x metal grease filter cassettes
- Grease filter saturation indicator
- Steel filter cover
- Inner frame

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 \varnothing 15 cm:
 - max. Normal use 430 m³/h
 - Intensive 760 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 60 dB(A) re 1 pW (46 dB(A) re 20 μ Pa sound pressure)
 - Intensive: 72 dB(A) re 1 pW (58 dB(A) re 20 μ Pa sound pressure)
 - 3 power levels and 2 intensive settings
 -
 -
 - Automatic intensive revert
 - Automatic after running (10 minutes)
 - Noise max. Normal Level: 60 dB*
 - Extractor hose 150 mm
 - Dimensions (WxD): 600 x 500 mm
 - Dimensions exhaust air (HxWxD): 628-954 x 600 x 500 mm
 - Dimensions recirculating with cleanAir module (HxWxD): 809-1139 x 600 x 500 mm
 - Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
 - Light Intensity: 745 lux
 - Colour Temperature: 3500 K
 - Average Energy Consumption: 29.3 kWh/year*
 - Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
 - Blower Efficiency Class: A*
 - Lighting Efficiency Class: A*
 - Grease Filtering Efficiency Class: C*

* In accordance with the EU-Regulation No 65/2014