

## IQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94PBC50B



Pyramid design extractor hood with a high extraction rate.

✓ LED lights: for optimal visibility and ambience while cooking.

### Features

#### Technical Data

Typology: ..... Wall-mounted  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: ..... 553-730/573-730 mm  
 Height of the appliance: ..... 246 mm  
 Minimum distance above an electric hob: ..... 550 mm  
 Minimum distance above a gas hob: ..... 650 mm  
 Weight: ..... 10.8 kg  
 Type of control: ..... mechanical  
 Number of speed settings: ..... 3  
 Maximum output air extraction: ..... 365 m³/h  
 Maximum output recirculating air: ..... 213 m³/h  
 Maximum Air flow: ..... 365 m³/h  
 Number of lights: ..... 2  
 Noise level: ..... 65 dB(A) re 1 pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable aluminium  
 EAN code: ..... 4242003801314  
 Connection Rating: ..... 100 W  
 Fuse protection: ..... 10 A  
 Nominal power: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... GB plug  
 Installation type: ..... Wall-mounted



### Optional accessories

LZ52751	Standard odor filter (replacement)
LZ12240	Chimney extension 500 mm
LZ12340	Chimney extension 750 mm
LZ50960	Backboard 90x65cm
LZ50961	Backboard 90 x 72 cm
LZ52750	Standard recirculation kit

## IQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94PBC50B

### Features

#### Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 365 m<sup>3</sup>/h
- Noise max. Normal Level: 65 dB\*

#### Features

- Push button control for extractor speeds and light
- 3 x power levels
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- 3 x metal grease filter cassettes - dishwasher safe
- For wall mounted installation

#### Design

- Chimney hood
- Mechanical

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Maximum extraction rate exhaust air 365 m<sup>3</sup>/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 65 dB(A) re 1 pW
- Extraction rate in recirculation mode:
  - Max. normal use: 213 m<sup>3</sup>/h
  - Noise level in recirculation mode:
    - Max. normal use: 67 dB(A) re 1 pW (54 dB(A) re 20 μPa sound pressure)
- Power rating: 100 W
- Light Intensity: 94 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 799-975 x 900 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 799-975 x 900 x 500mm
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*
- Average Energy Consumption: 53.1 kWh/year\*

#### Optional accessories

- Recirculating kit LZ52751

\* In accordance with the EU-Regulation No 65/2014

**IQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94PBC50B**

**Dimensioned drawings**

