

## iQ300, wall-mounted cooker hood, 90 cm, Stainless steel LC97BE532B

A+



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 730 m<sup>3</sup>/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ At 41 dB the hood is extremely quiet when being used.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

### Features

#### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, G-Mark, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 582-894/582-1004  
 Height of product, without chimney (mm) : 60  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 18.468  
 Type of control : Electronic  
 Maximum output air extraction (m<sup>3</sup>/h) : 460  
 Boost position output recirculating (m<sup>3</sup>/h) : 430  
 Maximum output recirculating air (m<sup>3</sup>/h) : 350  
 Boost position air extraction (m<sup>3</sup>/h) : 730  
 Number of lights : 3  
 Noise level (dB(A) re 1 pW) : 55  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable aluminium  
 EAN code : 4242003651346  
 Connection Rating (W) : 139  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 60; 50  
 Plug type : GB plug  
 Installation typology : Wall-mounted

### Optional accessories

LZ57300	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53451	Active carbon filter
LZ53450	Recirculating kit
LZ50961	Backboard 90 x 72 cm
LZ12365	Chimney extension 1500 mm
LZ12265	Chimney extension 1000 mm
LZ00XXP00	CleanAir act.carbon filter regenerative



## iQ300, wall-mounted cooker hood, 90 cm, Stainless steel LC97BE532B

### Features

#### Design

- 90 cm wide
- Day/night glass and metal fascia
- Soft touch button control for extractor speeds and light
- Height adjustable chimney sections
- For wall mounted installation

#### Key features

- Electronic control
- 3 x LED lights
- 3 x metal grease filter cassettes - dishwasher safe
- Steel filter cover
- Additional noise reduction insulation
- Soft touch button control with illuminated buttons

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 460 m<sup>3</sup>/h
  - Intensive 730 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 55 dB (A) re 1pW (41 dB (A) re 20 µPa sound pressure)
- 3 x power levels plus intensive setting
- Automatic intensive revert
- Adjustable automatic after running

#### Optional accessories

- Re-circulating kit - LZ52450