


iQ700, wall-mounted cooker hood, 90 cm, clear glass black printed LC97FVW60B



Flat design extractor hood with high extraction rate for a powerful performance.

- ✓ Brushless motor: powerful and quiet extraction of steam.
- ✓ cookConnect System: Control your extractor hood directly from your Cooktop (with matching cooktop).
- ✓ The climateControl Sensor monitors steam and odours and adjusts the power level automatically.
- ✓ emotionLight Pro: Adapt your extractor hood to your style.
- ✓ Home Connect: Remote access to a selection of features of your extractor hood via smartphone or tablet. (only in countries where Home Connect service is available).

Features

Technical Data

Typology : Chimney  
Approval certificates : CE, G-Mark, VDE  
Length electrical supply cord (cm) : 130  
Height of product, without chimney (mm) : 430  
Minimum distance above an electric hob : 450  
Minimum distance above a gas hob : 600  
Net weight (kg) : 22.866  
Type of control : Electronic  
Number of speed settings : 3-stage + 2 intensive  
Maximum output air extraction (m<sup>3</sup>/h) : 394  
Boost position output recirculating (m<sup>3</sup>/h) : 527.0  
Boost position air extraction (m<sup>3</sup>/h) : 717  
Number of lights : 2  
Noise level (dB(A) re 1 pW) : 57  
Diameter of air outlet (mm) : 120 / 150  
Grease filter material : Washable aluminium  
EAN code : 4242003759837  
Connection Rating (W) : 150  
Current (A) : 10  
Voltage (V) : 220-240  
Frequency (Hz) : 50; 60  
Plug type : GB plug  
Installation typology : Wall-mounted

Optional accessories

LZ56200	CleanAir active carbon filter spare part
LZ10AXL50	Chimney extension 1500 mm
LZ10AXK50	Chimney extension 1000 mm
LZ10AFU00	Standard recirculation kit
LZ10AFT00	Standard recirculation kit (chimless)
LZ10AFS00	Long Life recirculation kit
LZ10AFR00	Long Life recirculation kit (chimless)
LZ10AFA00	Standard odor filter (replacement)
LZ00XXP00	Long Life odor filter (replacement)



## iQ700, wall-mounted cooker hood, 90 cm, clear glass black printed LC97FVW60B

### Features

#### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 394 m³/h
- Intensive 717 m³/h
- Noise max. Normal Level: 57 dB\*

#### Features

- climateControl sensor
- emotionLight pro: Ambient light
- Boost function
- cookConnect hob based hood control

#### Home Connect: Remote Monitoring and Control (only in countries where Home Connect service is available)

- 3 power levels and 2 intensive settings
- SoftLight with dimmer function
- 2 x
- Colour Temperature: 3500 K
- Efficient BLDC motor
- Twin channel high performance fan motor
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- 2 x metal grease filter cassettes
- Grease and charcoal filter saturation indicators
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

#### Design

- Black glass
- Flat design
- Chimney hood
- touchControl for extractor speeds and light
- Electronic control

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- In recirculation operation chimless use possible
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Easy installation system
- Max. extraction rate: 717 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 394 m³/h
- Intensive 717 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 294 m³/h
- Intensive: 527 m³/h
- Noise max. Normal Level: 57 dB\*
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 57 dB(A) re 1 pW (44 dB(A) re 20 µPa sound pressure)
- Intensive: 70 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
- Noise levels in recirculation mode:
- Max. normal use: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)

- Intensive: 73 dB(A) re 1 pW (60 dB(A) re 20 µPa sound pressure)
- 
- 
- Light Intensity: 589 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 969-1239 x 890 x 263 mm
- Dimensions recirculating, chimney (HxWxD): 1029-1299 x 890 x 263 mm
- Dimensions recirculating, chimless (HxWxD): 500 mm x 890 x 263 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 1159 x 890 x 263 mm - mounting with outer chimney
- 1229-1499 x 890 x 263 mm - mounting with telescopic chimney
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 40 kWh/year\*

#### Optional accessories

- Recirculating kit

\* In accordance with the EU-Regulation No 65/2014