

iQ700, wall-mounted cooker hood, 90 cm, Stainless steel LC98BA572B

A



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 860 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 41 dB the hood is extremely quiet when being used.

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 19.213
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 460
 Boost position output recirculating (m³/h) : 440.0
 Boost position air extraction (m³/h) : 860
 Number of lights : 3
 Noise level (dB(A) re 1 pW) : 55
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable stainless steel
 EAN code : 4242003675366
 Connection Rating (W) : 169
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation typology : Wall-mounted

Optional accessories

LZ57300	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53451	Standard odor filter (replacement)
LZ53450	Standard recirculation kit
LZ50961	Backboard 90 x 72 cm
LZ12365	Chimney extension 1500 mm
LZ12265	Chimney extension 1000 mm
LZ00XXP00	Long Life odor filter (replacement)



4 242003 675366

iQ700, wall-mounted cooker hood, 90 cm, Stainless steel LC98BA572B

Features

Design

- 90 cm wide
- Stainless Steel
- White electronic display
- Electronic control via touchControl
- For wall mounted installation
- Designed for suspended or flush ceiling installation

Key Information

- touchControl for extractor speeds and light
- Boost function
- 3 x LED lights
- softLight with dimmer function
- 3 x metal grease filter cassettes - dishwasher safe
- Grease filter saturation indicator
- Steel filter cover
- Inner frame

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 460 m³/h
- Intensive 860 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 55 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure)
- Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Additional noise reduction insulation
- 3 power levels and 2 intensive settings
-
-
- Automatic intensive revert
- Automatic after running (10 minutes)
- Noise max. Normal Level: 55 dB*
- Extractor hose 150 mm
- Dimensions (WxD): 900 x 500 mm
- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating with cleanAir module (HxWxD): 809-1139 x 900 x 500 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 897 lux
- Colour Temperature: 3500 K
- Average Energy Consumption: 37.2 kWh/year*
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*

* In accordance with the EU-Regulation No 65/2014