

**iQ500**  
**iQ 500**  
**Chimney hood**  
**LC98GB542B**

**A+**



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 700 m<sup>3</sup>/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

#### Features

##### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 581-897/581-1007  
 Height of product, without chimney (mm) : 57  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 19.679  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction (m<sup>3</sup>/h) : 430  
 Boost position output recirculating (m<sup>3</sup>/h) : 360  
 Maximum output recirculating air (m<sup>3</sup>/h) : 300  
 Boost position air extraction (m<sup>3</sup>/h) : 700  
 Number of lights : 2  
 Noise level (dB(A) re 1 pW) : 61  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable stainless steel  
 EAN code : 4242003651469  
 Connection Rating (W) : 166  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 60; 50  
 Plug type : GB plug  
 Installation typology : Wall-mounted

#### Optional accessories

|           |  |
|-----------|--|
| LZ57000   | cleanAir Recirculation Kit               |
| LZ56200   | CleanAir active carbon filter spare part |
| LZ53251   | Active carbon filter                     |
| LZ53250   | Recirculating kit                        |
| LZ12350   | Chimney extension 1500 mm                |
| LZ12250   | Chimney extension 1000 mm                |
| LZ00XXP00 | CleanAir act.carbon filter regenerative  |



**iQ500**  
**iQ 500**  
**Chimney hood**  
**LC98GB542B**

#### Features

##### Design

- 90 cm wide
- Soft touch button control for extractor speeds and light
- White electronic display
- Stainless steel hood with glass canopy
- Height adjustable chimney sections
- For wall mounted installation

##### Key Information

- Electronic control
- Electronic power level display
- LED lights
- SoftLight with dimmer function
- 1 x metal grease filter cassette
- Steel filter cover
- Soft touch button control with 7-segment display
- Grease and charcoal filter saturation indicators

##### Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 430 m<sup>3</sup>/h
  - Intensive 700 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 61 dB (A) re 1pW (47 dB (A) re 20 µPa sound pressure)
- 3 power levels and 2 intensive settings
- Automatic intensive revert
- Adjustable automatic after running

##### Accessories

- Re-circulating kit - LZ53250