

## iQ700 LC98KC652B



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 730 m<sup>3</sup>/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

### Features

#### Technical Data

Color chimney : Stainless steel  
 Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 582-920/582-1030  
 Height of product, without chimney (mm) : 387  
 Minimum distance above an electric hob : 400  
 Minimum distance above a gas hob : 500  
 Net weight (kg) : 24.109  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction (m<sup>3</sup>/h) : 410  
 Boost position output recirculating (m<sup>3</sup>/h) : 380  
 Maximum output recirculating air (m<sup>3</sup>/h) : 310  
 Boost position air extraction (m<sup>3</sup>/h) : 730  
 Number of lights : 2  
 Noise level (dB(A) re 1 pW) : 58  
 Diameter of air outlet (mm) : 150 / 120  
 Grease filter material : Washable stainless steel  
 EAN code : 4242003651414  
 Connection Rating (W) : 166  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GB plug  
 Installation typology : Wall-mounted

### Optional accessories

LZ57000	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53251	Active carbon filter
LZ53250	Recirculating kit
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ00XXP00	CleanAir act.carbon filter regenerative



## iQ700

### LC98KC652B

#### Features

##### Design

- 90 cm wide
- Soft touch button control for extractor speeds and light
- White electronic display
- Blue indicator lights
- Black glass canopy
- Height adjustable chimney sections
- For wall mounted installation

##### Key Information

- Electronic control
- Electronic power level display
- climateControl Sensor
- LED lights
- SoftLight with dimmer function
- 2 x metal grease filter cassettes
- Steel filter cover
- Soft touch button control with 7-segment display
- Boost function
- Grease and charcoal filter saturation indicators

##### Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 410 m<sup>3</sup>/h
  - Intensive 730 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 µPa sound pressure)
- 3 power levels and 2 intensive settings
- Automatic intensive revert

##### Optional accessories

- Re-circulating kit - LZ53250