

**IQ100, Integrated cooker hood,
60 cm, Silver
LE66MAC00B**



This fold-out integrated hood with a high extraction rate for powerful performance is hidden in the upper cabinet unit.

✓ LED lights: for optimal visibility and ambience while cooking.

Features

Technical Data

Typology: Built-in/Built-under
 Length electrical supply cord: 150.0 cm
 Minimum distance above an electric hob: 500 mm
 Minimum distance above a gas hob: 650 mm
 Weight: 10.7 kg
 Type of control: mechanical
 Number of speed settings: 3
 Maximum output air extraction: 625 m³/h
 Maximum output recirculating air: 416 m³/h
 Maximum Air flow: 625 m³/h
 Number of lights: 2
 Noise level: 70 dB(A) re 1 pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material: Washable aluminium
 EAN code: 4242003806500
 Connection Rating: 256 W
 Fuse protection: 10 A
 Nominal power: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation type: Wall-mounted



Optional accessories

LZ10IMA00 Standard odor filter

IQ100, Integrated cooker hood, 60 cm, Silver LE66MAC00B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 625 m³/h
- Noise max. Normal Level: 70 dB*

Features

- Push button control for extractor speeds and light
- 3 x power levels
- 2 x 3W LED
- 2 x metal grease filter cassettes

Design

- Integrated hood
- Installation between cupboards
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 68.4 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating, chimney (HxWxD): 402-402 x 599 x 271 mm

Optional accessories

- Recirculating kit LZ10IMA00

* In accordance with the EU-Regulation No 65/2014

**IQ100, Integrated cooker hood,
60 cm, Silver
LE66MAC00B**

Dimensioned drawings

