

**iQ700, island cooker hood, 37 cm,  
Black  
LF31IVV60**



**Optional accessories**

LZ00XXP00 Long Life odor filter (replacement)

Extractor hood in cube design with high extraction rate for a powerful performance.

- ✓ The quiet high-performance motor: ensures efficient odour and steam removal.
- ✓ cookConnect system and climate control sensor: Perfect cooperation
- ✓ Home Connect: Access and control your hood, no matter where you are
- ✓ LED lights: For optimal visibility and ambience when cooking.
- ✓ Intensive setting starts automatically when you need it – Intensive setting with automatic revert.

**Features**

**Technical Data**

Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 140  
 Height of product, without chimney (mm) : 501  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 24.480  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Boost position output recirculating (m3/h) : 511.0  
 Number of lights : 4  
 Grease filter material : Washable aluminium  
 EAN code : 4242003761380  
 Connection Rating (W) : 272  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : no plug  
 Installation typology : Island



## iQ700, island cooker hood, 37 cm, Black LF31IVV60

### Features

#### Features

- cookConnect hob based hood control
- climateControl sensor
- Boost function
- 3 power levels and 2 intensive settings
- softLight with dimmer function
- 4 x 3w LED Light
- Colour Temperature: 3500 K
- Efficient BLDC motor
- Twin channel high performance fan motor
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- 1 x metal grease filter cassette
- Grease and charcoal filter saturation indicators
- Additional noise reduction insulation

#### Design

- Cable fixture for cube incl. ceiling mounting plate, easy installation only 4 screws, cable fixture length adjustable (20cm - 100cm)
- touchControl for extractor speeds and light
- Electronic control

#### Performance/technical information

- Suitable for recirculated extraction
- Extraction rate in recirculation mode: Max. normal use: 392 m³/h  
Intensive: 511 m³/h
- Noise levels in recirculation mode: Max. normal use: 69 dB(A) re 1 pW  
Intensive: 74 dB(A) re 1 pW
- Power rating: 272 W
- Light Intensity: 962 lux
- Electrical cable length 1.4 m
- Dimensions recirculating, chimney (HxWxD): 501-501 x 370 x 377 mm
- Dimensions recirculating, chimless (HxWxD): 501 mm x 370 x 377 mm

#### Optional accessories

- Recirculating kit LZ00XPP00

\* In accordance with the EU-Regulation No 65/2014

**iQ700, island cooker hood, 37 cm,  
Black  
LF31IVV60**

Dimensioned drawings

