


iQ700, island cooker hood, 90 cm, Stainless steel LF91BA582B



The ceiling-mounted island chimney hood is perfect for all kitchen islands.

- ✓ The 710 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 49 dB the hood is extremely quiet when being used.

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 698-878/698-998
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 32.527
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 570
 Boost position output recirculating (m³/h) : 500.0
 Boost position air extraction (m³/h) : 710
 Number of lights : 4
 Noise level (dB(A) re 1 pW) : 63
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 EAN code : 4242003675373
 Connection Rating (W) : 272
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation typology : Island

Optional accessories

LZ56200	CleanAir active carbon filter spare part
LZ12530	Extension for mounting kit 1000 mm
LZ12510	Extension for mounting kit 500 mm
LZ12410	Adapter for roof inclination front/back
LZ12385	Chimney extension 1600 mm
LZ12310	Adapter for roof inclination left/right
LZ12285	Chimney extension 1100 mm
LZ00XXP00	Long Life odor filter (replacement)



4 242003 675373

iQ700, island cooker hood, 90 cm, Stainless steel LF91BA582B

Features

Design

- 90 cm wide
- Stainless Steel
- White electronic display
- Electronic control via touchControl
- For ceiling mounted installation
- Designed for suspended or flush ceiling installation

Key Information

- touchControl for extractor speeds and light
- climateControl Sensor
- Boost function
- 4 x LED lights
- 3 x metal grease filter cassettes - dishwasher safe
- Grease filter saturation indicator
- Steel filter cover, Steel filter cover
- Rim ventilation
- Inner frame

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 570 m³/h
- Intensive 710 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 63 dB(A) re 1 pW (49 dB(A) re 20 µPa sound pressure)
- Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Additional noise reduction insulation
- 3 power levels and 2 intensive settings
-
-
- Automatic intensive revert
- Automatic after running (10 minutes)
- Noise max. Normal Level: 63 dB*
- Extractor hose 120 mm
- Dimensions (WxD): 900 x 600 mm
- Dimensions exhaust air (HxWxD): 744-924 x 900 x 600 mm
- Dimensions recirculating with cleanAir module (HxWxD): 812-1044 x 900 x 600 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 888 lux
- Colour Temperature: 3500 K
- Average Energy Consumption: 39.6 kWh/year*
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: A*

* In accordance with the EU-Regulation No 65/2014