

iQ500, island cooker hood, 90 cm, clear glass LF98GB542B



The ceiling-mounted island chimney hood is perfect for all kitchen islands.

- ✓ The 800 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 699-879/699-999
 Height of product, without chimney (mm) : 52
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 29.008
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 440
 Boost position output recirculating (m³/h) : 360.0
 Boost position air extraction (m³/h) : 800
 Number of lights : 4
 Noise level (dB(A) re 1 pW) : 58
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003651537
 Connection Rating (W) : 172
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation typology : Island



4 242003 651537

Optional accessories

LZ57500	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53650	Standard recirculation kit
LZ53251	Standard odor filter (replacement)
LZ12520	Extension for mounting kit 1000 mm
LZ12500	Extension for mounting kit 500 mm
LZ12375	Chimney extension 1600 mm
LZ12275	Chimney extension 1100 mm
LZ00XPO0	Long Life odor filter (replacement)

iQ500, island cooker hood, 90 cm,
clear glass
LF98GB542B

Features

Design

- 90 cm wide
- Soft touch button control for extractor speeds and light
- White electronic display
- Stainless steel hood with glass canopy
- Height adjustable chimney sections
- For ceiling mounted installation

Key Information

- Electronic control
- Electronic power level display
- LED lights
- SoftLight with dimmer function
- 1 x metal grease filter cassette
- Steel filter cover
- Soft touch button control with 7-segment display
- Grease and charcoal filter saturation indicators

Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 440 m³/h
 - Intensive 800 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW (44 dB (A) re 20 µPa sound pressure)
- 3 power levels and 2 intensive settings
- Automatic intensive revert
- Adjustable automatic after running