

iQ700, telescopic cooker hood, 90 cm, Stainless steel LI99SA683B

A



For clean lines the powerful telescopic cooker hood disappears into an upper cabinet, perfect for modern kitchens.

- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ The 959 m³/h extraction rate supplies clean air when cooking.
- ✓ At 44 dB the hood is extremely quiet when being used.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

Features

Technical Data

Typology : Pull-out
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 175
 Required niche size for installation (HxWxD) : 337mm x 524.0mm x 290mm
 Minimum distance above an electric hob : 430
 Minimum distance above a gas hob : 650
 Net weight (kg) : 15.431
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 503
 Boost position output recirculating (m³/h) : 795.0
 Boost position air extraction (m³/h) : 959
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 57
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 EAN code : 4242003777183
 Connection Rating (W) : 266
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation typology : Built-in

Optional accessories

LZ49600	Lowering frame
LZ49200	Installation kit for 90cm wide wall unit
LZ46830	CleanAir Recirculation Kit
LZ46810	CleanAir active carbon filter
LZ45650	Standard recirculation kit
LZ45610	Standard odor filter (replacement)
LZ10ITP00	Long Life odor filter (replacement)



4 242003 777183

iQ700, telescopic cooker hood, 90 cm, Stainless steel LI99SA683B

Features

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 502 m³/h
- Intensive 959 m³/h
- Noise max. Normal Level: 57 dB*

Features

- climateControl Sensor
- Boost function
- 3 power levels and 2 intensive settings
- softLight with dimmer function
- 2 x LED lights
- Colour Temperature: 3500 K
- Efficient BLDC motor
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- 3 x metal grease filter cassettes - dishwasher safe
- Grease and charcoal filter saturation indicators
- Additional noise reduction insulation
- For installation into 90cm wide cupboard

Design

- Extractor hood with telescopic canopy
- touchControl for extractor speeds and light
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 959 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 502 m³/h
- Intensive 959 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 493 m³/h
- Intensive: 795 m³/h
- Noise max. Normal Level: 57 dB*
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 57 dB(A) re 1 pW (44 dB(A) re 20 µPa sound pressure)
- Intensive: 71 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
- Noise levels in recirculation mode:
- Max. normal use: 68 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Intensive: 79 dB(A) re 1 pW (66 dB(A) re 20 µPa sound pressure)
-
-
- Light Intensity: 636 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.75 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions (HxWxD): 378 x 898 x 290 mm
- built-in dimensions (HxWxD): 337 x 524 x 290 mm

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 41.3 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014