

Series 6, Gas hob, 75 cm, Stainless steel PCQ7A5B90





Optional accessories

HEZ211310 Simmer cap
HEZ298105 Simmer plate
HEZ298107 Wok ring
HEZ298115 Small pot support

The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- FlameSelect: adjust the gas flame precisely using nine defined levels.
- Wok burner: powerful cooking at up to 4 kW.
- Continuous cast-iron pan support: for high firmness and stability of cookware.
- **Biomethane-ready**: your gas hob can also be powered with renewable biomethane gas.
- Sword knobs: for an ergonomic control.

Technical Data Product name/family:gas hob w integrated controls Built-in / Free-standing: Built-in Energy input:Gas Number of cooking zones:5 Type of control setting devices: sword knobs Min. required niche size for installation (HxWxD):45 x 560-562 x 480-492 mm Width of the appliance:750 mm Dimensions of the packed product (HxWxD): 145 x 793 x 597 mm Residual heat indicator: without Location of control panel: Front Color of surface: Stainless steel Length electrical supply cord: 100.0 cm Frequency: 50; 60 Hz





Series 6, Gas hob, 75 cm, Stainless steel PCQ7A5B90

The stainless-steel gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- FlameSelect: precisely control and adjust the flame in nine defined
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 gas burners
- Left front: economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 4 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 750 x 520
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 11.5 KW



Series 6, Gas hob, 75 cm, Stainless steel PCQ7A5B90

