Series 4, Gas hob, 60 cm, Stainless steel PGP6B5B60



Optional accessories

HEZ298105 Simmer plate HEZ298115 Small pot support

The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

- Continuous cast-iron finish pan supports: for maximum stability.
- **Biomethane-ready**: your gas hob can also be powered with renewable biomethane gas.
- Sword knobs: for an ergonomic control.
- Surface colour: elegant stainless-steel design.
- The seamless, one-piece stainless steel design makes cleaning Simple.

Technical Data

	recilineat Data	
F	Product name/family:gas	s hob w integrated controls
Е	Built-in / Free-standing:	Built-in
Е	Energy input:	Gas
	Number of cooking zones:	
7	Type of control setting devices:	sword knobs
Ν	Min. required niche size for installation (H	xWxD):45 x 560-562 x
4	480-492 mm	
	Width of the appliance:	
	Dimensions:	53 x 582 x 520 mm
	Dimensions of the packed product (HxWx[D): 141 x 651 x 578 mm
١	Net weight:	8.1 kg
(Gross weight:	9.0 kg
F	Residual heat indicator:	without
L	Location of control panel:	Front
Е	Basic surface material:	Stainless steel
(Color of surface:	Stainless steel
L	Length electrical supply cord:	100.0 cm
Е	EAN code:	4242002955346
(Gas connection rating:	7500 W
F	Fuse protection:	3 A
١	Voltage:	220-240 V
F	Frequency:	60; 50 Hz





Series 4, Gas hob, 60 cm, Stainless steel PGP6B5B60

The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

Design

- Stainless steel surface
- cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety


- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): $53 \times 582 \times 520$
- Required niche size for installation (HxWxD mm) : $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW



Series 4, Gas hob, 60 cm, Stainless steel PGP6B5B60



measurements in mm