

Series 6, Gas hob, 90 cm, Tempered glass, Black PPS9A6B90





Optional accessories

HEZ298127 Wok ring
HEZ298105 Simmer plate
HEZ298114 Small pot support

The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- FlameSelect: adjust the gas flame precisely using nine defined levels.
- Wok burner: powerful cooking at up to 4 kW.
- Standard and semi-flush built-in option: choose between flush or surface mounted installation.
- Semi-continuous cast-iron pan support: for high stability and easy cleaning.
- **Biomethane-ready**: your gas hob can also be powered with renewable biomethane gas.

Technical Data

Product name/family:gas hob w integrated con	trols
Built-in / Free-standing:Bu	ilt-in
Energy input:	.Gas
Number of cooking zones:	5
Type of control setting devices:sword k	nobs
Min. required niche size for installation (HxWxD):45 x 850-8	52 x
490-502 mm	
Width of the appliance:915	
Dimensions:58 x 915 x 520	mm
Dimensions of the packed product (HxWxD): 165 x 1116 x 659	mm
Net weight:21	.8 kg
Gross weight:	.0 kg
Residual heat indicator:wit	hout
Location of control panel:F	ront
Basic surface material:Tempered §	glass
Color of surface:E	3lack
Color of frame:E	3lack
Length electrical supply cord:150.0	0 cm
EAN code:4242002915	5067
Gas connection rating:1150	00 W
Fuse protection:	З А
Voltage:	40 V
Frequency: 60; 5	0 Hz





Series 6, Gas hob, 90 cm, Tempered glass, Black PPS9A6B90

The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Design

- Tempered glass surface, Black
- frameless: install the hob either flush or slightly raised on the worktop
- Cast iron pan supports with rubber feet

Usage convenience

- FlameSelect: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 gas burners
- Left: WOK burner up to 4 KW (depending on gas type)
- Center front: Economy burner up to 1 KW (depending on gas type)
- Center rear: Standard burner up to 1.75 KW (depending on gas type) $\,$
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): $58 \times 915 \times 520$
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 502)
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 11.5 KW

Series 6, Gas hob, 90 cm, Tempered glass, Black PPS9A6B90



