

Series 8, Induction hob with integrated ventilation system, 80 cm, surface mount with frame PXX875D34E













Optional accessories

HEZ39050 Wireless temperature sensor for cooktop, HEZ390511 Teppan Yaki (small), HEZ390512 Teppan Yaki (large), HEZ390522 Griddle Plate, HEZ394301 Connecting strip, HEZ9SE030 Set of 2 pots and 1 pan, HEZ381401 Exhaust kit, HEZ381501 Recirculating kit, HEZ381700 Recirculation filter, HEZ390011 Stainless Steel roaster with glas lid, HEZ390012 Steaming Rack for Stainless Steel roaste, HEZ390090 Wok Set consisting of 3 Items, HEZ390210 System pan diameter 15 cm, HEZ390220 System pan diameter 19 cm, HEZ390230 System pan diameter 21cm

The induction hob with integrated ventilation module: combines best induction with best ventilation technology for perfect results.

- Integrated ventilation module: extract steam and cooking odours at the source.
- DirectSelect Premium: spacious and intuitive touch interface.
- FlexInduction: more flexibility on your hob for large pots and pans.
- **PerfectAir sensor**: Automatic control of the hood settings for maximum extractor performance with minimal noise.
- PerfectCook: the sensor which can be adjusted, prevents overcooking and boiling over by precise controlling the cooking temperature.

Technical Data

Product name/family:	Cooking zone ceramic
Built-in / Free-standing:	Built-in
Energy input:	Electric
Min. required niche size for installation (HxW	xD):198 x 780-780 x
490-500 mm	
Width of the appliance:	
Dimensions:	198 x 816 x 527 mm
Dimensions of the packed product (HxWxD):	330 x 760 x 940 mm
Net weight:	28.6 kg
Gross weight:	34.9 kg
Residual heat indicator:	Separate
Location of control panel:	Front
Basic surface material:	Ceramic glass
Color of surface:	Black, Alu, brushed
Length electrical supply cord:	110.0 cm
Sealed Burners:	No
heating with booster:	All
Power of 2nd heating element (kW):	3.3 kW
Number of speed settings:	9-stage + intensive
Max. air extraction:	551 m³/h
Boost position output recirculating:	620.0 m³/h
Max. air recirculation:	557 m³/h
Boost position air extraction:	689 m³/h
Noise level:	70 dB(A) re 1 pW
Odour filter:	No
Operating Mode:	Convertible
Grease filter type:	Kassette
Voltage:	220-240 V
Frequency:	50; 60 Hz
Delay Shut off modes:	30 min



Series 8, Induction hob with integrated ventilation system, 80 cm, surface mount with frame PXX875D34E

The induction hob with integrated ventilation module: combines best induction with best ventilation technology for perfect results.

Design

- 816 mm
- Profile trim (front facette with side trim)

Control

- DirectSelect Premium touch control
- PerfectFry sensor with 5 temperature settings
- PerfectCook sensor ready (sensor sold seperately)

Special features

- 4 induction cooking zones
- 2 Flex zones
- Variable 17-stage power settings for each zone
- PanBoost
- ReStart function
- QuickStart function
- Electronic display, red
- MoveMode: MoveMode (3 levels)
- Keep warm function
- Timer for all zones
- Timer shows how long the cooktop is in use Count up timer per cooktop

Quickness

- PowerBoost function for all zones

Power and size

- Cooking zones:
- 1 x Ø400 x 240 mm, 3.3 KW, Induction heating or 2 x Ø 240 mm, 200 mm
- Connected load: 7.4 KW
- Voltage: 220 240 V

Safety Features

- Individual energy consumption display
- 2 stage residual heat indicator for each zone
- Automatic pan recognition sensor
- Safety cut-out switch-off Control panel lock Freeze function
- Main on/off switch

Technical information

- Min. worktop thickness: 20 mm (Installation in thinner worktops is also possible with the spare part: 626792)
- Cable included
- Length wire connection: 110 cm
- Measurement: (H/W/D) 198 x 816 x 527 mm
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D) $\,$
- Average Energy Consumption: 53.5 kWh/year
- Blower Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 39/69 dB
- Induction cooktop with integrated downdraft extractor
- Suitable for ducted or re-circulated extraction (Accessory is respectively needed)



- For ducted extraction extraction kit (accessory HEZ381401) needed
- For recirculated extraction cleanAir recirculating kit (accessory HEZ381501) needed
- Fully-automatic extraction functionality with Automatic Air Sensor



Series 8, Induction hob with integrated ventilation system, 80 cm, surface mount with frame PXX875D34E

