

Serie | 4
SMS46MW00G white
ActiveWater Dishwasher 60cm
Freestanding,

A++


- **ExtraDry:** extra drying option for difficult-to-dry loads.
- **Glass 40°C:** protective program for gently cleaning and drying glasses.
- **VarioFlex-baskets and VarioDrawer:** enhanced flexibility options with more space on all levels.

Technical Data

Water consumption (l) :	9.5
Built-in / Free-standing :	Free-standing
Height of removable worktop (mm) :	30
Depth with open door 90 degree (mm) :	1155
Adjustable feet :	Yes - front only
Maximum adjustability feet (mm) :	20
Net weight (kg) :	48.612
Gross weight (kg) :	51.0
Connection Rating (W) :	2400
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Length electrical supply cord (cm) :	175
Plug type :	GB plug
Length inlet hose (cm) :	150
Length outlet hose (cm) :	190
EAN code :	4242005041534
Number of place settings :	14
Energy efficiency class (2010/30/EC) :	A++
Energy consumption annual (kWh/annum) - NEW (2010/30/EC) :	266.00
Energy consumption (kWh) :	0.93
Power consumption in left-on mode (W) - NEW (2010/30/EC) :	0.10
Power consumption in off-mode (W) - NEW (2010/30/EC) :	0.10
Water consumption annual (l/annum) - NEW (2010/30/EC) :	2660
Drying performance :	A
Reference programme :	Eco
Total cycle time of reference programme (min) :	210
Noise level (dB(A) re 1 pW) :	46
Installation typology :	Built-under



4 242005 041534

Serie | 4 Dishwashers

SMS46MW00G white **ActiveWater Dishwasher 60cm** **Freestanding,**

Performance

- Energy Efficiency Class: A++
- Capacity: 14 place settings. VarioDrawer on 3rd level
- Energy consumption in Eco 50 programme: 266 kWh per year, based on 280 standard cleaning cycles
- Water consumption in Eco 50 programme: 2660 litres per year, based on 280 standard cleaning cycles
- Programme time in Eco 50 programme: 210 minutes
- A rated performance for washing and A for drying
- Noise level dB (A) re 1pW: 46 dB
- Power consumption off-mode / left-on mode: 0.1 W / 0.1 W

Programmes/functions

- 6 programmes: Intensive 70 °C, Auto 45-65 °C, Eco 50 °C, Glass 40 °C, Quick 45 °C, Prerinse
- 3 special options: VarioSpeedPlus, HygienePlus, Extra Dry
- Machine Care Programme

Flexible design elements

- varioFlex basket system
- VarioDrawer - loading of cutlery on 3rd level
- 3 stage Rackmatic height-adjustable top basket
- 2 foldable plate racks in top basket
- 4 foldable plate racks in bottom basket, and 2 foldable cup racks in bottom basket
- 2 foldable cup shelves in top basket and 2 foldable cup racks in bottom basket

Innovations and technology

- Heat exchanger - Hygienic and efficient drying
- DosageAssist detergent dispenser
- EcoSilence BLDC drive
- Automatic detergent detection
- AquaSensor III, Load Sensor

Design features

- Electronic time delay: 1-24 hours with remaining programme time indicator (min), water inlet indicator
- Leak protection system
- LED salt refill indicator, LED rinse aid refill indicator
- Self-cleaning filter system with 3 piece corrugated filter
- Child safety - Childproof door lock., tamperproof controls
- Dimensions (HxWxD): 84.5 x 60 x 60cm
- Efficiency information relates to the Eco 50 programme. This programme is suitable for cleaning normally soiled tableware and is the most efficient programme in terms of combined energy and water consumption.