

Serie | 4
WTH83000GB
Condenser tumble dryer with heat pump

A⁺

- **Energy efficiency class:**A+
- **Sensitive Drying system:** soft, even drying thanks to the unique drum structure.
- **Noise Level 65 dB:** dries quietly.
- **ECARF Quality Seal:** specially developed for the needs of allergy sufferers and sensitive skin.
- **EasyClean Filter:** easy cleaning of the condenser filter

Technical Data

Built-in / Free-standing :	Free-standing
Removable top :	No
Door hinge :	Right
Length electrical supply cord (cm) :	145.0
Height of removable worktop (mm) :	842
Dimensions of the product (mm) :	842 x 598 x 599
Net weight (kg) :	45.654
Fluorinated greenhouse gases :	Yes
Type of refrigerant :	R134a
Hermetically sealed equipment :	Yes
Quantity of fluorinated gases (kg) :	0.215
The quantity expressed in CO2 equivalent (t) :	0.307
EAN code :	4242002854397
Connection Rating (W) :	600
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Approval certificates :	CE, VDE
Capacity cotton (kg) - NEW (2010/30/EC) :	8.0
Standard cotton programme :	Cotton cupboard dry
Energy efficiency class (2010/30/EC) :	A+
Energy consumption electric dryer, full load - NEW (2010/30/EC) (kWh) :	2.22
Standard cotton programme time at full load (min) :	224
Energy consumption electric dryer, partial load - NEW (2010/30/EC) (kWh) :	1.25
Standard cotton programme time at partial load (min) :	130
Weighted annual energy consumption, electric dryer - NEW (2010/30/EC) (kWh) :	270.0
Weighted programme time (min) :	170
Average condensation efficiency full load (%) :	83
Average condensation efficiency partial load (%) :	79
Weighted condensation efficiency (%) :	81



4 242002 854397

Serie | 4 Tumble Dryer

WTH83000GB

Condenser tumble dryer with heat pump

Performance

- Energy efficiency class: A+
- Capacity: 8 kg
- Energy consumption 270.0 kWh per year, based on 160 drying cycles of the standard cotton programme at full and partial load, and the consumption of the low-power modes. Actual energy consumption per cycle will depend on how the appliance is used
- Energy consumption of the standard cotton programme at full load 2.22 kwh and energy consumption of the standard cotton programme at half load 1.25 kwh
- Power consumption in off-mode 0.1 W and in left-on mode 0.5 W
- The programme Cottons cupboard dry used at full and partial load is the standard drying programme to which the information in the label and the fiche relates, this programme is suitable for drying normal wet cotton laundry and is the most efficient programme in terms of energy consumption for cotton.
- Weighted programme time of the standard cotton programme at full and partial load: 170 min.
- Programme time of the standard cotton programme at full load 224 min and programme time of the standard cotton programme at partial load 130 min.
- Condensation efficiency class B on a scale from G (least efficient) to A (most efficient).
- Average condensation efficiency of the standard cotton programme at full load 83 % and average condensation efficiency of the standard cotton programme at partial load 79 %.
- Weighted condensation efficiency for the standard cotton programme at full and partial load: 81 %.
- Noise level: 65 dB (A) re 1 pW

Programmes/functions

- Fully electronic control dial for sensor drying programmes and timed programmes
- Special programmes: Woollens, Mixed Load, Towels, Time prog. 30 min. cold, Timed program 30 min. warm, Sportswear, Down, Super Quick 40, shirts/blouses
- Touch control buttons: start/pause, Reduced ironing, Fine-tuning for drying level, 24 hour Time Delay

Key features

- Sensitive drying: large galvanised drum and revolution drying system
- AntiVibration design: for greater stability and quietness
- Protection filter for condenser

Additional features

- LED Display for remaining time and 24 hours time delay, programme status indication, special functions
- Container for condensed water
- Warning for fluff filter and condensed water filter
- Anti crease cycle 120 minutes at the end of the programme
- Buzzer to indicate the end of cycle
- Child Lock
- Metal door catch

Technical Information

- Dimensions (H x W x D): 84.2 x 59.8 x 59.9 cm
- slide-under installation
- 2/G-control door plastic white