

Series 4, island cooker hood, 120 cm, Stainless Steel DIB128G50I



DHZ5477 Active carbon filter

With its stainless steel finish, this high performer complements any island hob in form and function.

• Ducted or Non-ducted Options

Typology:Island/Ceiling
 Height of product, without chimney: 340 mm
 Net weight: 29.4 kg
 Type of control:Electronic
 Number of speed settings: 3-stages + intensive setting
 Boost position output recirculating: 575.0 m³/h
 Max. air recirculation: 545 m³/h
 Boost position air extraction: 705 m³/h
 Number of lights: 4
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable stainless steel
 Odour filter: No
 Operating Mode: Convertible
 Optional accessories: DHZ5477
 Type of lamps used: LED
 Total power of the lamps: 4 W
 Clean filter reminders: No
 Voltage: 230 V
 Frequency: 50 Hz
 Plug type: India plug (6 Ampere)
 Installation typology: Island
 Material body: Stainless steel
 Plug type: India plug (6 Ampere)
 Dimensions of the product, with chimney (if exists) (in): x x
 Dimensions of the packed product: 18.50 x 29.92 x 51.37
 Net weight: 65.000 lbs
 Gross weight: 94.000 lbs
 Motor location: Integrated motor in hood chimney
 No-return airflow flap: No
 Dimensions of the product, with chimney (if exists): x 1175.0 x 610.0 mm
 Dimensions of the packed product (HxWxD): ... 470 x 760 x 1305 mm
 Net weight: 29.4 kg
 Gross weight: 42.6 kg



4 242002 973586

Series 4, island cooker hood, 120 cm, Stainless Steel DIB128G50I

With its stainless steel finish, this high performer complements any island hob in form and function.

Design

- Box design for Ceiling mounting
- Brushed stainless steel and glass panel
- Electronic touch control on black full width glass panel, on one side
- Chromed logo strip on the chimney
- Sleek white LED indication of settings

Key Functions

- Maximum extraction rate according to EN 61591: 705 m³/h
- Maximum blower performance: 745 m³/h (freeblowing)
- 4 fan speed settings (three plus intense)

Comfort

- 4 x 4 W LED lighting
- Intensive speed automatically switches back to previous setting after 10 minutes
- 4 metal grease filters, high grade stainless steel Baffle filters
- Noise level from 55 dB to 77 dB

Technical information

- For Ceiling mounting only
- Suitable for ducted or recirculating operation
- Dimensions of the product, with chimney (if exists)
- (HxWxD mm): 1000 x 1175 x 610
- Minimum clearance to gas/electric cook top: 750 mm
- Length electrical supply cord: 150 cm
- Ducting connection: 150mm/120mm diameter

* In accordance with the EU-Regulation No 65/2014

Series 4, island cooker hood, 120 cm, Stainless Steel
DIB128G50I

