

iQ500, wall-mounted cooker hood, 120 cm, Stainless steel LC28BH542



LZ12265	Chimney extension 1000 mm
LZ12365	Chimney extension 1500 mm
LZ53450	Standard recirculation kit
LZ53451	Standard odor filter (replacement)
LZ56200	CleanAir active carbon filter spare part
LZ57300	cleanAir Recirculation Kit

The wall-mounted chimney hood with high extraction rate – perfect for installing on the kitchen wall.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Intensive setting revert - Peak performance when steam escapes, and an automatic revert after a few minutes.
- ✓ Pleasantly quiet - motor.
- ✓ Intensive setting with automatic after revert setting

Color chimney: Stainless steel
Typology: Wall-mounted
Length electrical supply cord: 130.0 cm
Height of the chimney: 582-894/582-1004 mm
Height of product, without chimney: 60 mm
Net weight: 22.1 kg
Type of control: Electronic
Number of speed settings: 3-stage + 2 intensive
Maximum output air extraction: 455 m³/h
Boost position output recirculating: 430.0 m³/h
Maximum output recirculating air: 340 m³/h
Boost position air extraction: 830 m³/h
Number of lights: 4
Noise level: 53 dB(A) re 1pW
Diameter of air outlet: 150 / 120 mm
Grease filter material: Washable stainless steel
Odour filter: No
Air circulation: Convertible
Optional accessories: LZ12265, LZ12365, LZ53450, LZ53451, LZ56200, LZ57300
Type of lamps used: LED
Total power of the lamps: 12 W
Grease filter type: Multilayer cassette
Clean filter reminders: Yes
Connection Rating: 172 W
Fuse protection: 10 A
Voltage: 220-240 V
Frequency: 50; 60 Hz
Plug type: Gardy plug w/ earthing
Type: Wall-mounted
Material body: Stainless steel
Plug type: Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in): x x
Dimensions of the packed product: 22.83 x 24.01 x 51.57
Net weight: 49.000 lbs
Gross weight: 73.000 lbs
Motor location: Integrated motor in hood chimney
No-return airflow flap: Yes
Length electrical supply cord: 130.0 cm
Dimensions of the product, with chimney (if exists): 642-1064 x 1200.0 x 500.0 mm
Dimensions of the packed product (HxWxD): . 580 x 610 x 1310 mm
Net weight: 22.1 kg
Gross weight: 33.1 kg



iQ500, wall-mounted cooker hood, 120 cm, Stainless steel LC28BH542

- Energy Efficiency Class: A+
- Average Energy Consumption: 32.5 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Noise min./max. Normal Level: 44/53 dB

Design

- Appliance colour: stainless steel

Comfort

Technical information

- Suitable for ducted and re-circulating operation only
- For wall mounted installation
- Chimney hood wall fixing system
- Recirculation kit or clean air kit indicator available
- White electronic display
- Push button with 7-segment display
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Twin channel high performance fan motor
- 850EE
- 4 x LED 3W
- Light dimmer function
- Softlight with dimmer function
- Steel filter cover
- Steel filter cover, dishwasher safe
- Saturation display filter: grease- and charcoal filter
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 440 m³/h
- Intensive 830 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use: 54 dB(A) re 1 pW (40 dB(A) re 20 µPa sound pressure)
- Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Additional noise reduction insulation

Dimensions:

- Dimensions exhaust air (HxWxD): 642-954 x 1200 x 500 mm
- Dimensions recirculating (HxWxD): 642-1064 x 1200 x 500 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Recirculation kit or clean air kit
- 120 cm Chimney hood

iQ500, wall-mounted cooker
hood, 120 cm, Stainless steel
LC28BH542

