

## iQ500, wall-mounted cooker hood, 60 cm, Stainless steel LC68BF542



LZ00XXP00	Long Life odor filter (replacement)
LZ12250	Chimney extension 1000 mm
LZ12350	Chimney extension 1500 mm
LZ50660	Backboard 60 x 65 cm
LZ53250	Standard recirculation kit
LZ53251	Standard odor filter (replacement)
LZ56200	CleanAir active carbon filter spare part
LZ57000	cleanAir Recirculation Kit

The wall-mounted chimney hood with high extraction rate – perfect for installing on the kitchen wall.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Extremely quiet – The quiet hood that keeps the calm your kitchen.
- ✓ Intensive setting revert - Peak performance when steam escapes, and an automatic revert after a few minutes.
- ✓ Pleasantly quiet - motor.
- ✓ Intensive setting with automatic after revert setting

Typology: ..... Wall-mounted  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: ..... 582-908/582-1018 mm  
 Height of product, without chimney: ..... 46 mm  
 Net weight: ..... 19.9 kg  
 Type of control: ..... Electronic  
 Number of speed settings: ..... 3-stage + 2 intensive  
 Maximum output air extraction: ..... 430 m³/h  
 Boost position output recirculating: ..... 380.0 m³/h  
 Maximum output recirculating air: ..... 300 m³/h  
 Boost position air extraction: ..... 760 m³/h  
 Number of lights: ..... 2  
 Noise level: ..... 60 dB(A) re 1pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Air circulation: ..... Convertible  
 Optional accessories: ..... LZ00XXP00, LZ12250, LZ12350, LZ50660, LZ53250, LZ53251, LZ56200, LZ57000  
 Type of lamps used: ..... LED  
 Total power of the lamps: ..... 6 W  
 Grease filter type: ..... Multilayer cassette  
 Clean filter reminders: ..... Yes  
 Connection Rating: ..... 166 W  
 Fuse protection: ..... 10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... Gardy plug w/ earthing  
 Type: ..... Wall-mounted  
 Material body: ..... Stainless steel  
 Plug type: ..... Gardy plug w/ earthing  
 Dimensions of the product, with chimney (if exists) (in): ..... x x  
 Dimensions of the packed product: ..... 23.03 x 25.59 x 26.37  
 Net weight: ..... 44.000 lbs  
 Gross weight: ..... 45.000 lbs  
 Motor location: ..... Integrated motor in hood chimney  
 No-return airflow flap: ..... No  
 Length electrical supply cord: ..... 130.0 cm  
 Dimensions of the product, with chimney (if exists): ..... 628-1064 x 600.0 x 500.0 mm  
 Dimensions of the packed product (HxWxD): ... 585 x 650 x 670 mm  
 Net weight: ..... 19.9 kg  
 Gross weight: ..... 20.4 kg



## iQ500, wall-mounted cooker hood, 60 cm, Stainless steel LC68BF542

### Design

- Appliance colour: stainless steel
- White electronic display
- Push button with 7-segment display

### Technical information

- 60 cm Chimney hood
- Suitable for ducted and re-circulating operation only
- For wall mounted installation
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Twin channel high performance fan motor
- 850EE
- 2 x LED 3W
- Light dimmer function
- Softlight with dimmer function
- Steel filter cover, dishwasher safe
- Steel filter cover
- Saturation display filter: grease- and charcoal filter
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use: 430 m<sup>3</sup>/h
  - Intensive: 760 m<sup>3</sup>/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
  - Max. normal use: 60 dB(A) re 1 pW (46 dB(A) re 20 µPa sound pressure)
  - Intensive: 72 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)

### Dimensions:

- Dimensions exhaust air (HxWxD): 628-954 x 600 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 600 x 500 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Recirculation kit or clean air kit
- Total Connected load: 166 W

**iQ500, wall-mounted cooker hood, 60 cm, Stainless steel LC68BF542**

