


iQ700, wall-mounted cooker hood, 90 cm, Stainless steel LC91BA572

A



The wall-mounted chimney hood with high extraction rate – perfect for installing on the kitchen wall.

- ✓ The 690 m3/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert after 6 min.
- ✓ Extremely quiet at a mere 52 dB.

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Net weight (kg) : 21.213
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m3/h) : 560
 Boost position output recirculating (m3/h) : 470.0
 Boost position air extraction (m³/h) : 690
 Number of lights : 3
 Noise level (dB) : 66
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 Odour filter : No
 Operating Mode : Convertible
 Delay Shut off modes : 10M
 Optional accessories : LZ00XP00, LZ12265, LZ12365, LZ50960, LZ56200, LZ57300
 Type of lamps used : LED
 Total power of the lamps (W) : 9
 Grease filter type : Multilayer
 Connection Rating (W) : 269
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted
 Material body : Stainless steel
 Approval certificates : CE, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product (in) : 23.03 x 25.59 x 38.18
 Net weight (lbs) : 47
 Gross weight (lbs) : 59
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : No
 Length electrical supply cord (cm) : 130
 Dimensions of the product, with chimney (if exists) (mm) : 628-954 x 900.0 x 500.0
 Dimensions of the packed product (HxWxD) (mm) : 585 x 650 x 970
 Net weight (kg) : 21.213
 Gross weight (kg) : 27.0



4 242003 675663

iQ700, wall-mounted cooker hood, 90 cm, Stainless steel LC91BA572

Features

Design:

- 90 cm Stainless steel Box slimline brand design Table ventilation hood
- White electronic display
- Touch control with 7-segment display

Features:

- Energy Efficiency Class: A
- Suitable for ducted and re-circulating operation
- Total power of motors: 260 W
- Chimney hood wall fixing system
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
 - Intensive: 71 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
- Clean Air recirculating kit indicator available
- Fan regulation: 3-stage + 2 intensive
- Main switch: On/Off Control
- Intensive op. revert dur.: 6 min.
- Boost function
- Twin channel high performance fan motor
- 1000EE
- 3 x LED 3W
- Light dimmer function
- Softlight with dimmer function
- Cascade Filter
- Rim ventilation having Mat
- Rim extraction
- 3 x metal grease filter cassettes
- Saturation display filter: grease- and charcoal filter
- Maximum extraction power 690 m³/h
- Noise level: 52 dba
- Additional noise reduction insulation

Dimensions:

- Dimensions exhaust air (HxWxD): 628-954 x 90 cm x 50 cm
- Dimensions recirculating with cleanAir module (HxWxD);
- 689 x 900 x 500 mm - mounting with outer chimney
- 809-1139 x 900 x 500 mm - mounting with telescopic chimney
- Diameter pipe: 12 cm
- Total Connected load: 269 W
- Connecting cable 130 cm