

iQ500, Wall-Mounted Cooker Hood, 90 cm, Stainless steel LC97BIP50I



LZ00XPP00	Long Life odor filter (replacement)
LZ10FXJ05	Long Life recirculation kit
LZ11CXI16	Clean Air Plus recirculation kit
LZ12265	Chimney extension 1000 mm
LZ12365	Chimney extension 1500 mm
LZ12CBI14	Clean Air Standard recirculation kit
LZ12CXC56	Clean Air Plus recirc. kit external
LZ12FXD51	Long Life recirculation kit external
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ32CBB14	Clean Air Standard odor filter (repl.)
LZ50960	Backboard 90x65cm
LZ50961	Backboard 90 x 72 cm

The powerful wall hood convinces with a high extraction rate and an outstanding design.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ LED light: Optimal visibility and atmosphere when cooking.
- ✓ The power level and the LED light can be selected directly – touchControl
- ✓ Pleasantly quiet - motor.
- ✓ Intensive setting with automatic after revert setting

Color chimney:	Stainless steel
Typology:	Wall-mounted
Length electrical supply cord:	130.0 cm
Height of the chimney:	582-908/568-1018 mm
Height of product, without chimney:	46 mm
Net weight:	20.0 kg
Type of control:	Electronic
Number of speed settings:	3-stage + 2 intensive
Maximum output air extraction:	427 m³/h
Boost position output recirculating:	442 m³/h
Maximum output recirculating air:	343 m³/h
Boost position air extraction:	702 m³/h
Number of lights:	3
Noise level:	55 dB(A) re 1pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable stainless steel
Odour filter:	No
Air circulation:	Convertible
Optional accessories:	LZ00XPP00, LZ10FXJ05, LZ11CXI16, LZ12265, LZ12365, LZ12CBI14, LZ12CXC56, LZ12FXD51, LZ31XXB16, LZ32CBB14, LZ50960, LZ50961
Type of lamps used:	LED
Grease filter type:	Multilayer cassette
Clean filter reminders:	Yes
Connection Rating:	145 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	India plug (6 Ampere)
Type:	Wall-mounted
Material body:	Stainless steel
Plug type:	India plug (6 Ampere)
Dimensions of the product, with chimney (if exists) (in):	x x
Dimensions of the packed product:	23.03 x 25.59 x 38.18
Net weight:	44.000 lbs
Gross weight:	59.000 lbs
Motor location:	Integrated motor in hood chimney
No-return airflow flap:	Yes
Length electrical supply cord:	130.0 cm
Dimensions of the product, with chimney (if exists):	614-1064 x 898.0 x 500.0 mm
Dimensions of the packed product (HxWxD):	585 x 650 x 970 mm
Net weight:	20.0 kg
Gross weight:	26.6 kg



iQ500, Wall-Mounted Cooker Hood, 90 cm, Stainless steel LC97BIP50I

Design

- Box design
- 90 cm stainless steel Box design hood
- For wall mounted installation
- Appliance colour: stainless steel
- Touch control with 7-segment display

Performance

- 3 speeds plus 2 intensive
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use: 427 m³/h
- Intensive: 702 m³/h
- Extraction rate in recirculation mode:
- Max. normal use: 373 m³/h
- Intensive: 522 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use: 55 dB(A) re 1 pW (42 dB(A) re 20 µPa sound pressure)
- Intensive: 66 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)
- Noise levels in recirculation mode:
- Max. normal use: 66 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)
- Intensive: 73 dB(A) re 1 pW (60 dB(A) re 20 µPa sound pressure)

Comfort

- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Boost function
- easy to clean inner frame
- Light dimmer function
- Softlight with dimmer function
- Efficient BLDC-technology
- 3 x 1.5W LED
- Saturation display filter: grease- and charcoal filter
- Steel filter cover
- Additional noise reduction insulation
- Back-pressure flap: Yes
- Energy Efficiency Class: A
- Average Energy Consumption: 33.8 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

Technical Information

- Suitable for ducted and re-circulating operation only
- Chimney hood wall fixing system
- Recirculation kit or clean air kit
- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):

- 689 x 898 x 500 mm - mounting with outer chimney
- 795-1139 x 898 x 500 mm - mounting with telescopic chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Total Connected load: 145 W
- Connecting cable 130 cm
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014

iQ500, Wall-Mounted Cooker
Hood, 90 cm, Stainless steel
LC97BIP50I

