

iQ500, wall-mounted cooker hood, 90 cm, clear glass black printed LC98KLV601



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.


- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Detects steam and odours to adjust the power level automatically – climateControl sensor with cookConnect system
- ✓ voiceControl – Control hood functions and lighting using your voice.
- ✓ Home Connect – The app that makes your hood work smarter.
- ✓ LED light: Optimal visibility and atmosphere when cooking.

- LZ11AXE61 Chimney standard black
- LZ31XXB16 Clean Air Plus odor filter (replacement)
- LZ00XXP00 Long Life odor filter (replacement)
- LZ10AKR00 Long Life recirculation kit (chimless)
- LZ10AKS00 Long Life recirculation kit
- LZ10AXK50 Chimney extension 1000 mm
- LZ10AXL50 Chimney extension 1500 mm
- LZ11AKB16 Clean Air Plus odor filter (replacement)
- LZ11AKI16 Clean Air Plus recirculation kit
- LZ11AKV16 Clean Air Plus recirc. kit (chimless)
- LZ11AXC56 Clean Air Plus recirc. kit external

Typology: Wall-mounted
 Length electrical supply cord: 130.0 cm
 Height of product, without chimney: 323 mm
 Net weight: 22.4 kg
 Type of control: Electronic
 Number of speed settings: 3-stage + 2 intensive
 Maximum output air extraction: 468 m³/h
 Boost position output recirculating: 460 m³/h
 Maximum output recirculating air: 378 m³/h
 Boost position air extraction: 836 m³/h
 Number of lights: 2
 Noise level: 56 dB(A) re 1 pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable aluminium
 Odour filter: No
 Air circulation: Convertible
 Optional accessories: LZ11AXE61, LZ31XXB16, LZ00XXP00, LZ10AKR00, LZ10AKS00, LZ10AXK50, LZ10AXL50, LZ11AKB16, LZ11AKI16, LZ11AKV16, LZ11AXC56
 Type of lamps used: LED
 Grease filter type: Multilayer cassette
 Connection Rating: 163 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: India plug (10 Ampere)
 Type: Wall-mounted
 Material body: Glass, Lacquered
 Plug type: India plug (10 Ampere)
 Dimensions of the product, with chimney (if exists) (in): x x
 Dimensions of the packed product: 27.16 x 29.13 x 40.94
 Net weight: 49.000 lbs
 Gross weight: 69.000 lbs
 Motor location: Integrated motor in hood body
 No-return airflow flap: Yes
 Length electrical supply cord: 130.0 cm
 Dimensions of the product, with chimney (if exists): .. 452 x 890.0 x 499.0 mm
 Dimensions of the packed product (HxWxD): . 690 x 740 x 1040 mm
 Net weight: 22.4 kg
 Gross weight: 31.1 kg
 Delay Shut off modes: 10 min



iQ500, wall-mounted cooker
hood, 90 cm, clear glass black
printed
LC98KLV60I



Variant

- LC98KLV60I black
- For wall mounted installation
- Inclined glass brand design

Design

- black Inclined glass brand design
- Touch control with LED, 2x7-segment
- Steel filter cover, dishwasher safe

Technical information

- 3 speeds plus 2 intensive
- Maximum extraction power 489 m³/h (freeblowing)
- 2 x LM3-01_LED_1,5W
- Suitable for ducted and re-circulating operation only
- Recirculation kit or clean air kit

Comfort

- Noise min./max. Normal Level: 45/56 dB
- Light Intensity: 238 lux
- Colour Temperature: 3500 K

Dimensions:

- 90 cm black Inclined glass brand design hood
- Dimensions exhaust air (HxWxD): 928-1198 x 890 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 890 x 499 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

iQ500, wall-mounted cooker hood, 90 cm, clear glass black printed LC98KLV60I

