

**iQ700, island cooker hood, 90 cm,  
Stainless steel  
LF91BUV50I**



LZ22CXC56 Clean Air Plus recirc. kit external, LZ22FXD51 Long Life recirculation kit external, LZ31XXB16 Clean Air Plus odor filter (replacement), LZ32CBB14 Clean Air Standard odor filter (repl.), LZ53451 Standard odor filter (replacement), LZ53850 Standard recirculation kit, LZ00XXP00 Long Life odor filter (replacement), LZ12285 Chimney extension 1100 mm, LZ12310 Adapter for roof inclination left/right, LZ12385 Chimney extension 1600 mm, LZ12410 Adapter for roof inclination front/back, LZ12510 Extension for mounting kit 500 mm, LZ12530 Extension for mounting kit 1000 mm, LZ22CBI14 Clean Air Standard recirculation kit

The island hood convinces with a very high extraction rate in a distinguished design that perfectly matches your kitchen.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Detects steam and odours to adjust the power level automatically – climateControl sensor with cookConnect system
- ✓ voiceControl – Control hood functions and lighting using your voice.
- ✓ Home Connect – The app that makes your hood work smarter.
- ✓ LED light: Optimal visibility and atmosphere when cooking.

Typology: ..... Island/Ceiling  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: ..... 698-878/698-998 mm  
 Height of product, without chimney: ..... 46 mm  
 Net weight: ..... 29.8 kg  
 Type of control: ..... Electronic  
 Number of speed settings: ..... 3-stage + 2 intensive  
 Maximum output air extraction: ..... 598 m³/h  
 Boost position output recirculating: ..... 561 m³/h  
 Maximum output recirculating air: ..... 462 m³/h  
 Boost position air extraction: ..... 981 m³/h  
 Number of lights: ..... 4  
 Noise level: ..... 62 dB(A) re 1 pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Air circulation: ..... Convertible  
 Optional accessories: ..... LZ22CXC56, LZ22FXD51, LZ31XXB16, LZ32CBB14, LZ53451, LZ53850, LZ00XXP00, LZ12285, LZ12310, LZ12385, LZ12410, LZ12510, LZ12530, LZ22CBI14  
 Type of lamps used: ..... LED  
 Grease filter type: ..... Multilayer cassette  
 Connection Rating: ..... 266 W  
 Fuse protection: ..... 10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... India plug (6 Ampere)  
 Type: ..... Island  
 Material body: ..... Stainless steel  
 Plug type: ..... India plug (6 Ampere)  
 Dimensions of the product, with chimney (if exists) (in): ..... x x  
 Dimensions of the packed product: ..... 33.07 x 24.01 x 40.94  
 Net weight: ..... 66.000 lbs  
 Gross weight: ..... 89.000 lbs  
 Motor location: ..... Integrated motor in hood chimney  
 No-return airflow flap: ..... No  
 Length electrical supply cord: ..... 130.0 cm  
 Dimensions of the product, with chimney (if exists): ..... 744-1044 x 898.0 x 600.0 mm  
 Dimensions of the packed product (HxWxD): . 840 x 610 x 1040 mm  
 Net weight: ..... 29.8 kg  
 Gross weight: ..... 40.3 kg  
 Delay Shut off modes: ..... 10 min



**iQ700, island cooker hood, 90 cm,  
Stainless steel  
LF91BUV50I**

**Design**

- Island chimney hood
- 90 cm wide
- Appliance colour: stainless steel
- Electronic control via Touch control with 7-segment display

**Performance**

- 3 speeds plus 2 intensive
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use: 598 m³/h
- Intensive: 981 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use: 62 dB(A) re 1 pW (50 dB(A) re 20 µPa sound pressure)
- Intensive: 73 dB(A) re 1 pW (61 dB(A) re 20 µPa sound pressure)
- Extraction rate in recirculation mode:
- Max. normal use: 471 m³/h
- Intensive: 595 m³/h
- Noise levels in recirculation mode:
- Max. normal use: 72 dB(A) re 1 pW (60 dB(A) re 20 µPa sound pressure)
- Intensive: 77 dB(A) re 1 pW (64 dB(A) re 20 µPa sound pressure)

**Comfort**

- Cooktop-based hood control-based hood control
- (with matching cooktop)
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Boost function
- easy to clean innerframe
- Air quality sensor
- Light dimmer function
- Softlight with dimmer function
- Efficient BLDC-technology
- Saturation display filter: grease- and charcoal filter
- Steel filter cover, dishwasher safe

**Technical Information**

- Suitable for ducted and re-circulating operation only
- Recirculation kit or clean air kit
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Power rating: 266 W
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- India plug type

**Home Connect (only in countries where Home Connect service is available)**

- Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries

where this service is available)

iQ700, island cooker hood, 90 cm,  
Stainless steel  
LF91BUV50I

