

iQ500
LF98BE542 stainless steel
Island chimney hood
90 cm Stainless steel Box common
design hood

A+



The ceiling-mounted island chimney hood is perfect for all kitchen islands.

- ✓ The 870 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking
- ✓ Extremely quiet at a mere 40 dB.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert after 6 min.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, Eurasian, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 684-864/684-984
 Height of product, without chimney (mm) : 60
 Net weight (kg) : 29.107
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 460
 Boost position output recirculating (m³/h) : 430
 Maximum output recirculating air (m³/h) : 340
 Boost position air extraction (m³/h) : 870
 Number of lights : 4
 Noise level (dB) : 54
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable stainless steel
 Odour filter : No
 Operating Mode : Convertible
 Delay Shut off modes : 10M
 Optional accessories : LZ00XXP00, LZ12285, LZ12310, LZ12385, LZ12410, LZ12510, LZ12530, LZ53451, LZ53850, LZ56200, LZ57600
 Type of lamps used : LED
 Total power of the lamps (W) : 12
 Grease filter type : Multilayer cassette
 Connection Rating (W) : 172
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : Gardy plug w/ earthing
 Installation typology : Island
 Material body : Stainless steel
 Approval certificates : CE, Eurasian, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product (in) : 32.87 x 24.01 x 40.74
 Net weight (lbs) : 64
 Gross weight (lbs) : 83
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : Yes
 Length electrical supply cord (cm) : 130
 Dimensions of the product, with chimney (if exists) (mm) : 744-1044 x 900 x 600
 Dimensions of the packed product (HxWxD) (mm) : 835 x 610 x 1035
 Net weight (kg) : 29.107
 Gross weight (kg) : 38.0



iQ500
LF98BE542 stainless steel
Island chimney hood
90 cm Stainless steel Box common
design hood

Features

Design:

- 90 cm Stainless steel Box common design Table ventilation hood
- Soft touch button control with 7-segment display

White electronic display**Features:**

- Suitable for ducted and re-circulating operation
- Total power of motors: 160 W
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
 - Max. normal use: 54 dB(A) re 1 pW (40 dB(A) re 20 µPa sound pressure)
 - Intensive: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Fan regulation: 3-stage + 2 intensive
- Main switch: On/Off Control
- Intensive op. revert dur.: 6 min.
- 850EE
- Twin channel high performance fan motor
- 4 x LED 3W
- Softlight with dimmer function
- 3 x metal grease filter cassettes
- Steel filter cover
- Saturation display filter: grease- and charcoal filter
- Maximum extraction power 870 m3/h
- Noise level: 40 dba
- Additional noise reduction insulation
- Automatic intensive revert

Dimensions:

- Dimensions exhaust air (HxWxD): 744-924 x 90 cm x 60 cm
- Dimensions recirculating (HxWxD): 744-1044 x 90 cm x 60 cm
- Dimensions recirculating with cleanAir module (HxWxD): 812-1044mm x 90 cm x 60 cm
- Diameter pipe: 12 cm
- Connecting cable 130 cm
- Total Connected load: 172 W

iQ500
 LF98BE542 stainless steel
 Island chimney hood
 90 cm Stainless steel Box common
 design hood

Dimensioned drawings

