

**iQ300, telescopic cooker hood, 90 cm, Silver metallic LI97SA531I**



LZ49601 Lowering frame, LZ49850 Handle strip, LZ10ITP00 Long Life odor filter (replacement), LZ11ITD11 Long Life recirculation kit external, LZ11IXB16 Clean Air Plus odor filter (replacement), LZ11IXC16 Clean Air Plus recirc. kit external, LZ12ITB14 Clean Air Standard odor filter (repl.), LZ12ITI14 Clean Air Standard recirculation kit, LZ45610 Standard odor filter (replacement), LZ45650 Standard recirculation kit, LZ49200 Installation kit for 90cm wide wall unit, LZ49521 Handle strip white, LZ49561 Handle strip black

The telescopic cooker hood: practically disappears into your upper cabinet, giving you a sleek kitchen front.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ LED light: Optimal visibility and atmosphere when cooking.
- ✓ Pleasantly quiet - motor.
- ✓ Intensive setting with automatic after revert setting
- ✓ Pleasantly quiet - motor

Typology: ..... Pull-out  
 Length electrical supply cord: ..... 175.0 cm  
 Min. required niche size for installation (HxWxD): ..... 385mm x 524.0mm x 290mm mm  
 Net weight: ..... 12.2 kg  
 Type of control: ..... Electronic  
 Number of speed settings: ..... 3-stages + intensive setting  
 Maximum output air extraction: ..... 397 m³/h  
 Boost position output recirculating: ..... 628 m³/h  
 Maximum output recirculating air: ..... 358 m³/h  
 Boost position air extraction: ..... 729 m³/h  
 Number of lights: ..... 3  
 Noise level: ..... 53 dB(A) re 1 pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Air circulation: ..... Convertible  
 Optional accessories: ..... LZ49601, LZ49850, LZ10ITP00, LZ11ITD11, LZ11IXB16, LZ11IXC16, LZ12ITB14, LZ12ITI14, LZ45610, LZ45650, LZ49200, LZ49521, LZ49561  
 Type of lamps used: ..... LED  
 Total power of the lamps: ..... 6 W  
 Grease filter type: ..... Multilayer cassette  
 Connection Rating: ..... 146 W  
 Fuse protection: ..... 16 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 60; 50 Hz  
 Plug type: ..... India plug (16 Ampere)  
 Type: ..... Built-in into the cabinet  
 Material body: ..... zinc plated  
 Plug type: ..... India plug (16 Ampere)  
 Dimensions of the product, with chimney (if exists) (in): ..... x x  
 Dimensions of the packed product: ..... 15.74 x 37.00 x 19.29  
 Net weight: ..... 27.000 lbs  
 Gross weight: ..... 33.000 lbs  
 Motor location: ..... Integrated motor in hood body  
 No-return airflow flap: ..... Yes  
 Length electrical supply cord: ..... 175.0 cm  
 Dimensions of the product, with chimney (if exists): ..426 x 898.0 x 290.0 mm  
 Dimensions of the packed product (HxWxD): ... 400 x 940 x 490 mm  
 Net weight: ..... 12.2 kg  
 Gross weight: ..... 15.1 kg  
 Delay Shut off modes: ..... 10 min



## iQ300, telescopic cooker hood, 90 cm, Silver metallic LI97SA531I

### Variant

- LI97SA531I silver metallic lacquer
- For installation into a 60cm or 90cm wide cupboard

### Design

- silver metallic lacquer Standard
- Push button with LED
- Steel filter cover, dishwasher safe

### Technical information

- 3 x power levels plus intensive setting
- Maximum extraction power 415 m<sup>3</sup>/h (freeblowing)
- 3 x LM3-01\_LED\_1,5W
- Suitable for ducted and re-circulating operation only
- Recirculation kit or clean air kit

### Comfort

- Noise min./max. Normal Level: 41/53 dB
- Light Intensity: 355 lux
- Colour Temperature: 3500 K

### Dimensions:

- 90 cm silver metallic lacquer Standard hood
- Dimensions exhaust air (HxWxD): 426-426 x 898 x 290 mm
- Dimensions recirculating (HxWxD): 426-426 x 898 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

iQ300, telescopic cooker hood, 90 cm, Silver metallic  
LI97SA531I

