

**Series 4, island cooker hood, 90 cm,
Stainless steel
DIB97IM50**



B



DHZ1256 Chimney extension 1600 mm, DHZ5346 Standard odor filter (replacement), DHZ5385 Standard recirculation kit, DIZ2CB114 Clean Air Standard recirculation kit, DIZ2CX5C6 Clean Air Plus recirc. kit external, DIZ2FX5D1 Long Life recirculation kit external, DZZ0XX0P0 Long Life odor filter (replacement), DZZ1XX1B6 Clean Air Plus odor filter (replacement), DHZ1231 Adapter for roof inclination left/right, DHZ1241 Adapter for roof inclination front/back, DHZ1246 Chimney extension 1100 mm, DHZ1251 Extension for mounting kit 500 mm, DHZ1253 Extension for mounting kit 1000 mm, DZZ2CB1B4 Clean Air Standard odor filter (repl.), HEZG9AS00S Adapter

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **especially silent:** maximal extractor performance with minimal noise
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **TouchSelect control:** quick touch-control selection of desired settings and light.

Typology:Island/Ceiling
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 691-871/691-991 mm
 Height of product, without chimney: 53 mm
 Net weight: 29.2 kg
 Type of control:Electronic
 Number of speed settings: 3-stages + intensive setting
 Max. air extraction:438 m³/h
 Boost position output recirculating: 527 m³/h
 Max. air recirculation: 390 m³/h
 Boost position air extraction: 754 m³/h
 Number of lights: 4
 Noise level:57 dB(A) re 1 pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material:Washable aluminium
 Odour filter: No
 Operating Mode: Exhaust / Recirculation (Accessory available separately)
 Optional accessories: DHZ1256, DHZ5346, DHZ5385, DIZ2CB114, DIZ2CX5C6, DIZ2FX5D1, DZZ0XX0P0, DZZ1XX1B6, DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DZZ2CB1B4, HEZG9AS00S
 Type of lamps used: LED
 Grease filter type:Kassette
 Connection rating: 256 W
 Fuse protection:10 A
 Voltage: 220-240 V
 Frequency: 60; 50 Hz
 Plug type: Gardy plug w/ earthing
 Installation typology: Island
 Material body: Stainless steel
 Plug type: Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in):x x
 Dimensions of the packed product: 33.07 x 24.01 x 40.94
 Net weight:64.000 lbs
 Gross weight: 88.000 lbs
 Motor location: Integrated motor in hood chimney
 No-return airflow flap: Yes
 Length electrical supply cord: 130.0 cm
 Dimensions of the product, with chimney (if exists): 744-1044 x 898.0 x 600.0 mm
 Dimensions of the packed product (HxWxD): ... 840 x 610 x 1040 mm
 Net weight:29.2 kg
 Gross weight: 39.7 kg



Series 4, island cooker hood, 90 cm, Stainless steel DIB97IM50

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 74.3 kWh/year
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 45/57 dB

Variant:

Design:

Technical information

Performance

Power:

Environment and safety:

Comfort:

Measures:

Technical information

- Island Hood Brushed steel
- 90 cm wide
- 90 cm Island chimney hood, Brushed steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Ceiling mounted hood
- TouchControl
- Electronic controls
- TouchControl with Electronic display
- 3 speeds plus intensive setting via TouchControl
- Electronic controls via TouchControl with Electronic display
- TouchControl (3 speeds plus intensive setting) with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- easy to clean Innerframe
- Energy efficient capacitor motor
- 4 x 1,5 W LED
- Light Intensity: 409 lux
- Colour Temperature: 3500 K
- Cassette with alu frame
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 438 m³/h
 - Intensive 754 m³/h
- Extraction rate exhaust air according to EN 61591 max. 754 m³/h
- Extraction rate according to EN 61591 ø 15 cm:

- max. Normal use 438 m³/h
- Intensive 754 m³/h
- Extraction rate exhaust air according to EN 61591:
 - max. normal use 438 m³/h, intensive 754 m³/h
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD): 812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: Noise, max. speed in normal use: 57 dB dB(A) re 1 pW
- Noise level according to EN 60704-2-13 exhaust air:
 - Max. normal use: 57 dB(A) re 1 pW
 - Intensive: 68 dB(A) re 1 pW
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 754 m³/h
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Power rating: 256 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 390 m³/h
 - Intensive: 527 m³/h
 - Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW
 - Intensive: 73 dB(A) re 1 pW

* In accordance with the EU-Regulation No 65/2014

**Series 4, island cooker hood, 90 cm,
Stainless steel
DIB97IM50**

