

Series 6, built-in fridge with freezer section, 177.5 x 56 cm, flat hinge KIL82AFF0











KSZ10020 Bottle Rack
KSZB0S00 Heavy-duty hinge support

The refrigerator with A+++ rating, VitaFresh plus Box and TouchControl: especially efficient - keeps your fruits and vegetables vitamin-rich and fresh up to twice as long.

• LED lighting: keep your groceries in perfect view.

A ↑ G

- Easy Access Shelf: pull-out glass shelf gives you better access to the contents of your fridge.
- VarioShelf: space for bottles and bowls with sectioned glass shelves that can be separated and slid underneath.
- Super Cooling function: cools new food placed inside faster, thus protecting already cooled food.

Gross weight:	
Energy Efficiency Class (Regulation (EU) 2017/1369):	F
Average annual energy consumption in kilowatt hour per year	
(kWh/a):	
Sum of volume of frozen compartments:	Į Į
Sum of volume of chill compartments:	<u> </u>
Airborne acoustical noise emissions :36 dB(A) re 1 pV	W
Airborne acoustical noise emission class:	.C
Built-in / Free-standing:	in
Number of compressors:	.1
Number of independent cooling systems:	. 1
Width of the appliance:558 mi	m
Height:	m
Depth of the product:	m
Net weight:	
Min. required niche size for installation (HxWxD): 1775.0 x 560 x 55	50
mm	
Door panel options:	le
Door hinge:	le
Number of Adjustable Shelves in fridge compartment:	
Shelves for Bottles:	
Frost free system:	
Interior ventilator:	
Reversible Door Hinge: Ye	
Length electrical supply cord:	
Noise level:	
Multi-Flow Air Tower:	
Economy setting:	
Cold technology:	
Fast cooling switch:	es
Temperature Controlled Drawer:	
Humidity Control Drawer:	
Number of Door Bins - Refrigerator:	
Door bin adjustability - Refrigerator:	
Tilt-out door bins in fridge:	
Gallon wide door bins:	
Number of Gallon storage:	
Motorized Shelf:	
Material of the shelves:	
Door opened indicator freezer:	
Connection rating:	W
Fuse protection:	
Voltage:	
Frequency:	
Storage Period in Event of Power Failure (h):	
Door panel options:	
Installation typology: Integrate	
Noise level:	
Energy Star Qualified:	
Plug type:	
Required cutout/niche size for installation (in):	
riequired cutourymente size for mistattation (m):	٠,







Series 6, built-in fridge with freezer section, 177.5 x 56 cm, flat hinge KIL82AFF0

The refrigerator with A+++ rating, VitaFresh plus Box and TouchControl: especially efficient - keeps your fruits and vegetables vitamin-rich and fresh up to twice as long.

Performance and consumption

Design and Styling

- LED interior light in fridge section

Convenience & Safety

- 7 segment electronic control
- FreshSense constant temperature by intelligent sensor technology $% \left(1\right) =\left(1\right) \left(1\right$
- Automatic defrost in fridge section
- Acoustic open door warning system

Fridge Compartment

- 5 safety glass shelves (4 height adjustable), of which 1 x VarioShelf divisible and pushed under shelf, 1 x extendable EasyAccess shelf
- 5 door bins, there of 1x dairy compartment

Freshness System

- 1 VitaFresh plus drawer on telescopic rails with humidity control-Fruits and vegetables retain vitamins and stay fresh up to 2 times longer.
- Vegetable container on telescopic rails

Freezer Section

- 1hinged freezer compartment
- Ice compartment suited for Pizzas

Dimensions

- Dimensions (H x W x D): 177.2 cm x 55.8 cm x 54.5 cm
- Niche Dimension (H x W x D): 177.5 cm x 56.0 cm x 55.0 cm

Technical Information

- Door right hinged, reversible
- Connected load: 90 W
- Nominal voltage: 220 240 V

Accessories

- egg tray
- ice cube tray
- bottle holder

Country Specific Options

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.


Environment and Safety


Installation

General Information



Series 6, built-in fridge with freezer section, 177.5 x 56 cm, flat hinge KIL82AFF0







Maximal permissible weight of the unit fronts


Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges Å Weight A: Appliance door height including hinges in mm

- B: Undamped hinge, unit front in kg
- C: Damped hinge, unit front in kg
- D: Additional possible load in kg with heavy load kit

Α	В	C	ט
1500-1750	22	22	
720-1400	19	19	B+5 / C+5
A1	15	19	B+3 / C+3
A2	15	19	








measurements in mm

Maximal permissible weight of the unit fronts




Fitted kitchen unit doors that exceed the permissible weight may cause damage and result in functional impairment of the hinges.

of appliance door	undamped hinge,	damped hinge,
Hinges in mm:	Door in kg:	Door in kg:
1500-1750	22	22



measurements in mm Recommended gap dimensions for flat hinges



F	R X	
16-19	0-3	2.5
20	0-1	3
	2-3	2.5
21	0-1	3
	2-3	2.5
22	0	4
	1	3.5
	2-3	3

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.