


Series 6, Induction hob, 80 cm, , PVS851FB5E









HEZ390090 Wok Set consisting of 3 Items
HEZ9ES100 Espresso maker 4 cups
HEZ9FE280 Iron pan Ø 18 / 28 cm
HEZ9SE040 4 pieces Set
HEZ9SE060 6 pieces Set


- **DirectSelect**: Direct, simple selection of the desired cooking zone, power and additional functions.
- \bullet 28 cm cooking zone: for small and large pots and pans.
- **U-Bevel**: Elegant, appealing design with bevelled front and sides.
- PowerBoost: Up to 50% more power for faster heating.
- If you turn off the cooktop it saves the last selected setting for a short time. If the cooktop is switched of within a short time again the former settings are still available.

Product name/family:			
Width of the appliance:			
Dimensions:			
Dimensions of the packed product (HxWxD): 126 x 953 x 608 mm			
Net weight:			
Gross weight:			
Residual heat indicator:yes			
Location of control panel: Front			
Basic surface material:			
Color of surface:			
Length electrical supply cord:			
Sealed Burners:			
Power Boost:			
Power of 2nd heating element (kW):			
Power of 5th heating element (kW):			
Power of heating element (kW in boost):[3.7] kW			
Power of 5th heating element (kW in boost):[3.7] kW			
Connection rating:			
Voltage:			
Frequency: 50; 60 Hz			
Energy input:Electric			
Plug type:No plug (electrical connection by electrician)			
Appliance Dimensions (h x w x d) (in): x x			
Dimensions of the packed product: 4.96 x 23.93 x 37.51			
Net weight:			
Gross weight:			
Total number of positions that can be used at the same time: 4			
Length electrical supply cord:			
Min. required niche size for installation (HxWxD):51 x 750-750 x			
490-500 mm			
Dimensions: 51 x 802 x 522 mm			
Dimensions of the packed product (HxWxD): 126 x 953 x 608 mm			
Net weight:12.8 kg			
Gross weight:			






Series 6, Induction hob, 80 cm, , PVS851FB5E



(1) Ventilation gap must be present


All measurements in mm




- A: Minimum distance from the hob cut-out to the wall.
 B: Recessed depth
 C: The clearance between the surface of the worktop and the top of the front of the oven must be 30 mm. See space requirements for the oven.

The worktop into which the hob is installed must withstand loads of approx. 60 kg; suitable substructures must be used if required.

D	E	F
585-600	50	≥ 35
> 600	≥ 50	≥ 50





Measurements in mm