

**Series 6, Island Hood, 90 cm,  
Stainless steel  
DIB98JQ50B**



DIZ2CX5C6 Clean Air Plus recirc. kit external, DIZ2FX5D1 Long Life recirculation kit external, DZZ0XX0P0 Long Life odor filter (replacement), DZZ1XX1B6 Clean Air Plus odor filter (replacement), DZZ2CB1B4 Clean Air Standard odor filter (repl.), DHZ1231 Adapter for roof inclination left/right, DHZ1241 Adapter for roof inclination front/back, DHZ1246 Chimney extension 1100 mm, DHZ1251 Extension for mounting kit 500 mm, DHZ1253 Extension for mounting kit 1000 mm, DHZ1256 Chimney extension 1600 mm, DHZ5346 Standard odor filter (replacement), DHZ5385 Standard recirculation kit, DIZ2CB114 Clean Air Standard recirculation kit

**The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.**

- **PerfectAir sensor:** enjoy quieter, odour-free cooking.
- **Extra silent:** the high-performance hood, with minimal noise.
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **Eco Silence Drive:** the powerful, energy-saving drive for hoods.

Typology: .....Island/Ceiling  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: ..... 698-878/698-998 mm  
 Height of product, without chimney: .....46 mm  
 Net weight: .....28.7 kg  
 Type of control: .....Electronic  
 Number of speed settings: .....3-stage + 2 intensive  
 Max. air extraction: .....445 m<sup>3</sup>/h  
 Boost position output recirculating: .....457 m<sup>3</sup>/h  
 Max. air recirculation: ..... 353 m<sup>3</sup>/h  
 Boost position air extraction: ..... 867 m<sup>3</sup>/h  
 Number of lights: ..... 4  
 Noise level: .....54 dB(A) re 1 pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Ventilation mode: .....Convertible  
 Optional accessories: .....DIZ2CX5C6, DIZ2FX5D1, DZZ0XX0P0, DZZ1XX1B6, DZZ2CB1B4, DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DHZ5346, DHZ5385, DIZ2CB114  
 Type of lamps used: ..... LED  
 Grease filter type: .....Kassette  
 Connection rating: ..... 166 W  
 Fuse protection: .....10 A  
 Voltage: .....220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... GB plug  
 Installation typology: .....Island  
 Material of the body: .....Stainless steel  
 Plug type: ..... GB plug  
 Dimensions of the product, with chimney (if exists) (in): .....x x  
 Dimensions of the packed product: ..... 33.07 x 24.01 x 40.94  
 Net weight: .....63.000 lbs  
 Gross weight: ..... 86.000 lbs  
 Motor location: ..... Integrated motor in hood chimney  
 No-return airflow flap: ..... No  
 Length electrical supply cord: ..... 130.0 cm  
 Dimensions of the product, with chimney (if exists): ..... 744-1044 x 898.0 x 600.0 mm  
 Dimensions of the packed product (HxWxD): ... 840 x 610 x 1040 mm  
 Net weight: .....28.7 kg  
 Gross weight: ..... 39.2 kg  
 Delay shut off modes: ..... 10 min



## **Series 6, Island Hood, 90 cm, Stainless steel DIB98JQ50B**

**The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.**

---

### **Design**

- Island chimney hood, 90 cm
- 90 cm wide
- Appliance colour: Brushed steel
- Ceiling mounted hood
- Electronic controls via TouchControl

### **Operating mode / operation**

- 3-stage + 2 intensive
- Max. extraction rate: 867 m<sup>3</sup>/h
- Extraction rate according to DIN/EN 61591 ø 15 cm: max. Normal 445 m<sup>3</sup>/h Intensive 867 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air at normal use max.: 54 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 31.9 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Noise min./max. Normal Level: 44/54 dB\*

### **Comfort**

- Suitable for ducted or re-circulated extraction
- air quality sensor 1.1
- Cass.w.stainl. st. perf. plate
- Metal grease filter, dishwasher safe
- easy to clean yes
- Light dimmer function
- SoftLight
- 4 x 1,5W LED
- Light Intensity: 423 lux
- Colour Temperature: 3500 K

### **Technical information**

- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Connected load: 166 W
- Electrical cable length 1.3 m

\* In accordance with the EU-Regulation No 65/2014

**Series 6, Island Hood, 90 cm,  
Stainless steel  
DIB98JQ50B**

