

**Serie | 2, Wall-mounted cooker hood,  
90 cm  
DKE906HMY**



**The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.**

- **High efficiency grease filtration system:** pyramid filter and oil collector system.
- **Extraction rate:** at 860 m<sup>3</sup>/h, it quickly ensures optimal kitchen air quality, with connect pipe:160 mm inner diameter/175 mm outer diameter.
- **Especially quiet:** high performance at just 55 dB(sound pressure level),69 dB(A)(sound power level).
- **Halogen lighting:** for optimal, energy-efficient illumination of the hob.

**Technical Data**

Typology :	Chimney
Length electrical supply cord (cm) :	150
Net weight (kg) :	20.772
Type of control :	mechanical
Number of speed settings :	3
Number of lights :	2
Diameter of air outlet (mm) :	160
Odour filter :	No
Operating Mode :	Air extraction only
Type of lamps used :	Halogen
Total power of the lamps (W) :	40
Connection Rating (W) :	190
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Wall-mounted
Material body :	Glass, Stainless steel
Plug type :	GB plug
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	26.96 x 27.16 x 39.17
Net weight (lbs) :	46
Gross weight (lbs) :	71
Motor location :	Integrated motor in hood body
No-return airflow flap :	No
Length electrical supply cord (cm) :	150
Dimensions of the product, with chimney (if exists) (mm) :	600-840 x 895.0 x 505.0
Dimensions of the packed product (HxWxD) (mm) :	685 x 690 x 995
Net weight (kg) :	20.772
Gross weight (kg) :	32.0



4 242002 640068

## Serie | 2, Wall-mounted cooker hood, 90 cm DKE906HMY

**The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.**

---

### **Design**

- Chimney hood, 90 cm
- Appliance material: Stainless steel + white temper glass

### **Operation and power**

- Twin channel high performance fan motor
- Strong and smooth air flowing channel, efficient motor and impeller, better exhaust effect
- Professional oil collection channel, patented filter fast captures the condensed grease which then flows to the oil cup
- 3 speeds
- Suitable for ducted operation
- Maximum extraction rate exhaust air NO\_FEATURE m<sup>3</sup>/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air at normal use max.: 69 dB(A) re 1 pW (69 dB(A) re 20 µPa sound pressure)

### **Comfort**

- Double filter, highly effective exhaust and filtering
- Rocker switches for extractor speeds and light
- 2 x 20W halogen bulb

### **Technical Information**

- Appliance size (WxDxH): 895 mm x 505 mm x 600-840 mm
- Connected load: 190 W
- 160 mm diameter pipe

**Serie | 2, Wall-mounted cooker hood, 90 cm  
DKE906HMY**

