

**Serie | 6, Wall-mounted Hood, 90 cm,
Stainless steel
DWB091E50**

A⁺



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning

- **Extraction rate:** at 980 m³/h, it quickly ensures optimal kitchen air quality
- **Especially quiet:** high performance at just 48 dB
- **LED lighting:** for perfect, very energy-efficient illumination of the hob
- **Intensive speed setting with reset:** automatically resets the hood to normal speed setting after 6 min.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Net weight (kg) :	19.013
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	620
Boost position output recirculating (m ³ /h) :	490.0
Boost position air extraction (m ³ /h) :	980
Number of lights :	3
Noise level (dB(A) re 1 pW) :	62
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Delay Shut off modes :	10M
Optional accessories :	DHZ1223, DHZ1233, DHZ5345, DHZ5346, DSZ5201, DSZ6240, DZZ0XX0PC
Type of lamps used :	LED
Total power of the lamps (W) :	9
Grease filter type :	Kassette
Connection Rating (W) :	269
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	Gardy plug w/ earthing
Installation typology :	Wall-mounted
Material body :	Stainless steel
Approval certificates :	CE, VDE
Plug type :	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	23.03 x 25.59 x 38.18
Net weight (lbs) :	42
Gross weight (lbs) :	55
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	Yes
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	628-1064 x 900.0 x 500.0
Dimensions of the packed product (HxWxD) (mm) :	585 x 650 x 970
Net weight (kg) :	19.013
Gross weight (kg) :	24.8



4 242002 774763

Serie | 6, Wall-mounted Hood, 90 cm, Stainless steel DWB091E50

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom in
your kitchen planning**

Technical information

- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
689 x 900 x 500 mm - mounting with outer chimney
809-1139 x 900 x 500 mm - mounting with telescopic chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Connected load: 269 W

** In accordance with the EU-Regulation No 65/2014*

- Energy Efficiency Class: A+*
- Average Energy Consumption: 34.7 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Noise min./max. Normal Level: 44/62 dB*

Design

- Chimney hood
- 90 cm wide
- Wall mounted hood
- Electronic controls via Push button controls with digital display

Operation and power

- Twin channel high performance fan motor
- 3-stage + 2 intensive
- Extraction rate according to DIN/EN 61591 ø 15 cm: max.
Normal 620 m³/h Intensive 980 m³/h
- Extraction rate exhaust air according to EN 61591: max.
normal use 620m³/h, Intensive 980m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13
exhaust air at normal use max.: 62 dB(A) re 1 pW (62 dB(A) re
20 µPa sound pressure)

Environment and safety

- Metal grease filter, dishwasher safe

Comfort:

- Suitable for ducted or re-circulated extraction
- 3 x LED 3W
- Light dimmer function
- Light Intensity: 897 lux
- Colour Temperature: 3500 K
- 10 min.
- 6 min.
- Additional noise insulation

**Serie | 6, Wall-mounted Hood, 90 cm,
Stainless steel
DWB091E50**

