

**Serie | 8, Wall-mounted cooker hood,
120 cm, Stainless steel
DWB121K50**

A



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning

- **Extraction rate:** at 830 m³/h, it quickly ensures optimal kitchen air quality
- **LED lighting:** for perfect, very energy-efficient illumination of the hob
- **Intensive speed setting with reset:** automatically resets the hood to normal speed setting after 6 min.
- **Especially quiet:** high performance at just 49 dB

Technical Data

Typology :	Chimney
Approval certificates :	CE, Morocco, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Net weight (kg) :	24.350
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	633
Boost position output recirculating (m ³ /h) :	430.0
Boost position air extraction (m ³ /h) :	830
Number of lights :	4
Noise level (dB(A) re 1 pW) :	62
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
Odour filter :	No
Operating Mode :	Convertible
Delay Shut off modes :	10M
Optional accessories :	DHZ1223, DHZ1233, DHZ5345, DHZ5346, DSZ5201, DSZ6240
Type of lamps used :	LED
Total power of the lamps (W) :	12
Grease filter type :	Multilayer
Connection Rating (W) :	272
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	Gardy plug w/ earthing
Installation typology :	Wall-mounted
Material body :	Stainless steel
Approval certificates :	CE, Morocco, VDE
Plug type :	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	22.83 x 24.40 x 51.96
Net weight (lbs) :	54
Gross weight (lbs) :	78
Motor location :	Integrated motor in hood chimney
No-return airflow flap :	Yes
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	628-1064 x 1200.0 x 500.0
Dimensions of the packed product (HxWxD) (mm) :	580 x 620 x 1320
Net weight (kg) :	24.350
Gross weight (kg) :	35.4



Serie | 8, Wall-mounted cooker hood, 120 cm, Stainless steel DWB121K50

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning

- Energy Efficiency Class: A*
- Average Energy Consumption: 36.8 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Noise min./max. Normal Level: 44/63 dB*

Design

- Chimney hood
- 120 cm wide
- Wall mounted hood
- TouchControl for extractor speeds and light

Operation and power

- Twin channel high performance fan motor
- 3-stage + 2 intensive
- Extraction rate exhaust air according to EN 61591: max. normal use 650m³/h, Intensive 830m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air at normal use max.: 63 dB(A) re 1 pW (63 dB(A) re 20 µPa sound pressure)
- Air quality sensor

Environment and safety

- Rimm ventilation
- Metal grease filter, dishwasher safe
- Filter cover stainless steel

Comfort:

- Suitable for ducted or re-circulated extraction
- 4 x LED 3W
- Light dimmer function
- Light Intensity: 1167 lux
- Colour Temperature: 3500 K
- Additional noise insulation
- 10 min.
- 6 min.

Technical information

- Dimensions exhaust air (HxWxD): 628-954 x 1200 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 1200 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD): 689 x 1200 x 500 mm - mounting with outer chimney 809-1139 x 1200 x 500 mm - mounting with telescopic chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Connected load: 272 W

* In accordance with the EU-Regulation No 65/2014

**Serie | 8, Wall-mounted cooker hood, 120 cm, Stainless steel
DWB121K50**

