

**Series 6, Wall-mounted Hood, 90 cm,  
Stainless steel  
DWB98JQ50B**



DHZ1223	Chimney extension 1000 mm
DHZ1233	Chimney extension 1500 mm
DHZ5345	Standard recirculation kit
DHZ5346	Standard odor filter (replacement)
DWZ0XX0J5	Long Life recirculation kit
DWZ1CX1I6	Clean Air Plus recirculation kit
DWZ2CB1I4	Clean Air Standard recirculation kit
DWZ2CX5C6	Clean Air Plus recirc. kit external
DWZ2FX5D1	Long Life recirculation kit external
DZZ0XX0P0	Long Life odor filter (replacement)
DZZ1XX1B6	Clean Air Plus odor filter (replacement)
DZZ2CB1B4	Clean Air Standard odor filter (repl.)

**The wall-mounted chimney hood: mount it  
on the wall, giving you complete freedom  
in your kitchen planning**

- **Eco Silence Drive:** the powerful, energy-saving drive for hoods.
- **Extra silent:** the high-performance hood, with minimal noise.
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.**

Typology: .....Wall-mounted  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: ..... 582-908/568-1018 mm  
 Height of product, without chimney: ..... 46 mm  
 Net weight: ..... 19.3 kg  
 Type of control: .....Electronic  
 Number of speed settings: .....3-stage + 2 intensive  
 Max. air extraction: .....430 m<sup>3</sup>/h  
 Boost position output recirculating: ..... 457 m<sup>3</sup>/h  
 Max. air recirculation: ..... 353 m<sup>3</sup>/h  
 Boost position air extraction: ..... 844 m<sup>3</sup>/h  
 Number of lights: ..... 3  
 Noise level: ..... 55 dB(A) re 1 pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Ventilation mode: .....Convertible  
 Optional accessories: ..... DHZ1223, DHZ1233, DHZ5345, DHZ5346, DWZ0XX0J5, DWZ1CX1I6, DWZ2CB1I4, DWZ2CX5C6, DWZ2FX5D1, DZZ0XX0P0, DZZ1XX1B6, DZZ2CB1B4  
 Type of lamps used: ..... LED  
 Grease filter type: .....Kassette  
 Connection rating: ..... 165 W  
 Fuse protection: .....10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... GB plug  
 Installation typology: .....Wall-mounted  
 Material of the body: .....Stainless steel  
 Plug type: ..... GB plug  
 Dimensions of the product, with chimney (if exists) (in): .....x x  
 Dimensions of the packed product: ..... 23.03 x 25.59 x 38.18  
 Net weight: .....43.000 lbs  
 Gross weight: ..... 56.000 lbs  
 Motor location: .....Integrated motor in hood chimney  
 No-return airflow flap: ..... No  
 Length electrical supply cord: ..... 130.0 cm  
 Dimensions of the product, with chimney (if exists): ..... 614-1064 x 898.0 x 500.0 mm  
 Dimensions of the packed product (HxWxD): ..... 585 x 650 x 970 mm  
 Net weight: ..... 19.3 kg  
 Gross weight: ..... 25.6 kg  
 Delay shut off modes: ..... 10 min



## **Series 6, Wall-mounted Hood, 90 cm, Stainless steel DWB98JQ50B**

**The wall-mounted chimney hood: mount it  
on the wall, giving you complete freedom  
in your kitchen planning**

---

### **Design**

- 90 cm wide
- Wall mounted hood
- Electronic controls via TouchControl

### **Operating mode / operation**

- 3-stage + 2 intensive
- Extraction rate exhaust air according to EN 61591: max. normal use 430m<sup>3</sup>/h, Intensive 844m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air at normal use max.: 55 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Average Energy Consumption: 30.1 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*

### **Comfort**

- Suitable for ducted or re-circulated extraction
- air quality sensor 1.1
- Cass.w.stainl. st. perf. plate
- easy to clean yes
- Light dimmer function
- SoftLight
- 3 x 1,5W LED
- Light Intensity: 389 lux
- Colour Temperature: 3500 K

### **Technical information**

- Wall fixing system
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm
- Connected load: 165 W
- Electrical cable length 1.3 m

\* In accordance with the EU-Regulation No 65/2014

