

**Series 6, Island cooker hood, 90 cm,  
Stainless steel  
DIB98JQ50**



DHZ1231	Adapter for roof inclination left/right
DHZ1241	Adapter for roof inclination front/back
DHZ1246	Chimney extension 1100 mm
DHZ1251	Extension for mounting kit 500 mm
DHZ1253	Extension for mounting kit 1000 mm
DHZ1256	Chimney extension 1600 mm
DIZ2CB114	Clean Air Standard recirculation kit
DIZ2CX5C6	Clean Air Plus recirc. kit external
DIZ2FX5D1	Long Life recirculation kit external
DZZ0XX0P0	Long Life odor filter (replacement)
DZZ1XX1B6	Clean Air Plus odor filter (replacement)
DZZ2CB1B4	Clean Air Standard odor filter (repl.)

**The island chimney hood: Flexible ceiling  
mounting for your island kitchen**

- **PerfectAir sensor:** enjoy quieter, odour-free cooking.
- **Extra silent:** the high-performance hood, with minimal noise.
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **EcoSilence Drive:** the powerful, energy-saving drive for hoods.

Typology: ..... Island/Ceiling  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: ..... 698-878/698-998 mm  
 Height of product, without chimney: ..... 46 mm  
 Net weight: ..... 30.8 kg  
 Type of control: ..... Electronic  
 Number of speed settings: ..... 3-stage + 2 intensive  
 Max. air extraction: ..... 445 m<sup>3</sup>/h  
 Boost position output recirculating: ..... 457 m<sup>3</sup>/h  
 Max. air recirculation: ..... 353 m<sup>3</sup>/h  
 Boost position air extraction: ..... 867 m<sup>3</sup>/h  
 Number of lights: ..... 4  
 Noise level: ..... 54 dB(A) re 1pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable stainless steel  
 Odour filter: ..... No  
 Operating Mode: ..... Convertible  
 Optional accessories: ..... DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DHZ1256, DIZ2CB114, DIZ2CX5C6, DIZ2FX5D1, DZZ0XX0P0, DZZ1XX1B6, DZZ2CB1B4  
 Type of lamps used: ..... LED  
 Grease filter type: ..... Kasette  
 Clean filter reminders: ..... Yes  
 Connection rating: ..... 166 W  
 Fuse protection: ..... 10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... Gardy plug w/ earthing  
 Installation typology: ..... Island  
 Material body: ..... Stainless steel  
 Plug type: ..... Gardy plug w/ earthing  
 Dimensions of the product, with chimney (if exists) (in): ..... x x  
 Dimensions of the packed product: ..... 33.07 x 24.01 x 40.94  
 Net weight: ..... 68.000 lbs  
 Gross weight: ..... 91.000 lbs  
 Motor location: ..... Integrated motor in hood chimney  
 No-return airflow flap: ..... Yes  
 Length electrical supply cord: ..... 130.0 cm  
 Dimensions of the product, with chimney (if exists): ..... 744-1044 x 898.0 x 600.0 mm  
 Dimensions of the packed product (HxWxD): ... 840 x 610 x 1040 mm  
 Net weight: ..... 30.8 kg  
 Gross weight: ..... 41.5 kg



## Series 6, Island cooker hood, 90 cm, Stainless steel DIB98JQ50

### The island chimney hood: Flexible ceiling mounting for your island kitchen

- Energy Efficiency Class: A+
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Noise max. Normal Level: 54 dB\*

#### **Variant:**

#### **Design**

#### **Technical information:**

#### **Performance**

#### **Key Functions**

#### **Environment and safety:**

#### **Comfort:**

#### **Measures:**

#### **Technical information:**

- 90 cm Island Hood Hood, Silver metallic
- 90 cm wide
- 90 cm Island Hood, Stainless Steel
- Suitable for ducted or recirculating operation
- Recirc. kit or clean air kit
- Ceiling mounted hood
- TouchControl for extractor speeds and light
- electronic controls
- electronic controls via TouchControl with lightline
- TouchControl
- 3 fan speeds setting plus 2 intensive
- Automatic intensive revert after 6 min
- Automatic run on for 10 min.
- Easy to clean yes
- air quality sensor 1.1
- Dimmer function
- softLight
- Efficient BLDC-technology
- 4 x 1.5W LED
- Light Intensity: 423 lux
- Colour Temperature: 3500 K
- Saturation indicator for metal and charcoal filter
- removable metal grease filters
- Removable metal grease filter, dishwasher safe
- Max. extraction rate according to EN 61591: 867 m<sup>3</sup>/h
- Extraction rate according to EN 61591 max. 867 m<sup>3</sup>/h
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 445m<sup>3</sup>/h
- Intensive 867 m<sup>3</sup>/h
- 3 removable metal grease filters

- Max. noise level according to EN 60704-3 and EN 60704-2-13: 54 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 54 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure)
- Intensive: 69 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 867 m<sup>3</sup>/h
- Dimensions exhaust air (HxWxD mm): 744-924 x 898 x 600
- Dimensions recirculating (HxWxD mm): 744-1044 x 898 x 600
- Electrical connection rating: 166 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

\* In accordance with the EU-Regulation No 65/2014

**Series 6, Island cooker hood, 90 cm,  
Stainless steel  
DIB98JQ50**

