

Series 8, Built-in oven, 60 x 60 cm, Black HBG6764B6B











1 x combination grid, 1 x universal pan

HEZ327000 Pizza stone, HEZ530000 Half tray, HEZ531010 Baking tray, non-stick ceramic coated, HEZ532010 Universal pan, non-stick ceramic coated, HEZ617000 Pizza pan, enamelled, HEZ625071 Grill tray, anthracite, HEZ631070 Baking tray, enamelled, HEZ632070 Multipurpose pan, enamelled, HEZ633001 Lid for professional pan, enamelled, HEZ633070 Professional pan with grid, enamelled, HEZ634000 Baking and roasting grid, HEZ635000 Barbecue-Set, HEZ636000 Glass pan, HEZ638270 2 level telescopic rails, full ext,pyro, HEZ638370 3 level telescopic rails, full ext,pyro, HEZ660050 Cover Strip, HEZ664000 Baking and roasting grid, steam, HEZ915003 Glass roasting dish, 5,4 L

The built-in oven with PerfectBake and PerfectRoast: you get perfect baking and roasting results – automatically.

- PerfectBake: the easy way to perfect baking results.
- PerfectRoast: precise measurement of core temperature for a perfect roast.
- 4D Hot Air: even heat distribution for perfect results on any level.
- TFT touchscreen control: easy-to-use thanks to the control ring with full text and images.
- Pyrolytic self-cleaning: Automatically cleans the oven, just wipe out the ash.

| Gross weight: | _ |
|---|-----------------|
| Built-in / Free-standing: | |
| Integrated Cleaning system: Pyrol | |
| Min. required niche size for installation (HxWxD): 585- | 595 x 560-568 |
| x 550 mm | |
| Dimensions: | 5x594x548 mm |
| Dimensions of the packed product (HxWxD): 670 x | 670 x 680 mm |
| Control Panel Material: | Glass |
| Door Material: | Glass |
| Net weight: | 38.9 kg |
| Usable volume of cavity: | 71 l |
| Number of interior lights: | 1 |
| Length electrical supply cord: | 120.0 cm |
| Interior Lights - cavity 1: | 1 |
| Pull-out system: | 1-level |
| Included accessories:1 x combination grid, 1 x | x universal pan |
| Broil Element Wattages cavity 1: | 2800 W |
| Convection Element Wattages cavity 1: | 2200 W |
| Energy efficiency rating: | |
| Energy consumption per cycle conventional (2010/30/8 | EC):0.87 |
| kWh/cycle | |
| Energy consumption per cycle forced air convection (2) | 010/30/EC):69 |
| kWh/cycle | |
| Energy efficiency index (2010/30/EC): | 81.2 % |
| Connection rating: | |
| Fuse protection: | 16 A |
| Voltage: | |
| Frequency: | |
| Plug type: | |
| Alternative colors available: | |
| Energy input: | |
| Required cutout/niche size for installation (in): | |
| Dimensions of the packed product: 26.37 x | |
| Net weight: | |
| Gross weight: | |
| Length electrical supply cord: | |
| Net weight: | |
| <u> </u> | |





Series 8, Built-in oven, 60 x 60 cm, Black HBG6764B6B

The built-in oven with PerfectBake and PerfectRoast: you get perfect baking and roasting results – automatically.

Heating Functions

- Oven with 13 heating methods: 4D hot air, Hot Air-Eco, Conventional heat, Conventional heat ECO, Hot air grilling, Full width grill, Half width grill, Pizza setting, Bottom heat, Low temperature cooking, Defrost setting, Preheating, Keep warm
- Temperature range 30 °C 300 °C
- Cavity volume: 71 l

Hook-in racks / rails

- Number of shelf levels: 5 PC
- 1 level telescopic shelf, 3 level telescopic shelf rails full extension, Detend function, pyrolitic proof

Design

- Intuitive Control Ring
- Enamel cavity anthracite
- Extra large capacity oven

Cleaning

- Pyrolytic self-cleaning function
- Full glass inner door

Comfort

- LED display control (red)
- Electronic clock
- - Digital temperature display with proposal
- - Actual temperature display Heating-up indicator Sabbath setting
- Door hinge: Bottom, SoftClosing, Soft opening
- straight bar handle
- Supporting systems: Dish categories
- PerfectRoast multipoint temperature probe
- PerfectBakebaking sensor
- Rapid heating-up
- Halogen interior lighting switch for oven illumination
- Integral cooling fan
- HomeConnect ready on WLAN

Standard Accessories

- 1 x combination grid, 1 x universal pan

Safety Functions:

- Maximum window temperature 30° C low door temperature
- Low door temperature during pyrolitic cleaning.
- 4 layered glazed CoolTouch door
- Child lock, Residual heat indicator, Automatic switch off, Start and Stop button, door contact switch, Automatic door lock during pyrolysis

Technical Information

- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V


- Electrical connection rating: 3600 W
- Energy efficiency rating (acc. EU Nr. 65/2014): A+(at a range of energy efficiency classes from A+++ to D)
- Energy consumption per cycle in conventional mode:0.87 kWh
- Energy consumption per cycle in fan-forced convection mode:0.69 kWh
- Number of cavities: 1 Heat source: electrical Cavity volume:71 l

Technical information:

- Dimensions of the product (HxWxD mm): 595 x 594 x 548
- Required niche size for installation (HxWxD mm): $585 595 \times 560 568 \times 550$
- "Please reference the built-in dimensions provided in the installation drawing"



Series 8, Built-in oven, 60 x 60 cm, Black HBG6764B6B



measurements in mm

min. 550 min. 35

585+10

19,5

min. 35

60

595

595

594

548

Space for appliance connection 320 x 115

measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

| Hob type | min. worktop thickness | |
|-------------------------------|------------------------|-------|
| | fitted | flush |
| Induction hob | 37 mm | 38 mm |
| Full surface Induction hob | 47 mm | 48 mm |
| Gas hob | 30 mm | 38 mm |
| Electric hob | 27 mm | 30 mm |

