


## Series 2, Induction hob, 60 cm, Black, PUC61KAA5E









HEZ390090 Wok Set consisting of 3 Items
HEZ9ES100 Espresso maker 4 cups
HEZ9FE280 Iron pan Ø 18 / 28 cm
HEZ9SE030 Set of 2 pots and 1 pan
HEZ9SE040 4 pieces Set
HEZ9SE060 6 pieces Set

# The induction hob: cook fast, clean and safely while using very little energy.

- Power Boost: up to 35% faster heating compared to highest power level.
- Child Lock: locks the control panel to prevent unauthorized use.
- Induction Technology: saves in average 20% energy compared to radiant technology.
- Quick Start: start straight away and select the desired cooking level
- Touch Select Basic: easy selection of the desired cooking zone and setting of the power level.

| Product name/family: Cooking zone ceramic                            |  |  |  |
|--|--|--|--|
| Built-in / Free-standing:  |  |  |  |
| Energy input:Electric  |  |  |  |
| Total number of positions that can be used at the same time: 3       |  |  |  |
| Required niche size for installation (HxWxD): 51 x 560-560 x 490-500 |  |  |  |
| mm   |  |  |  |
| Width of the appliance:592 mm  |  |  |  |
| Dimensions: 51x592x522 mm  |  |  |  |
| Dimensions of the packed product (HxWxD): 126 x 753 x 603 mm         |  |  |  |
| Net weight:9.6 kg  |  |  |  |
| Gross weight:  |  |  |  |
| Residual heat indicator:   |  |  |  |
| Location of control panel: Front                                     |  |  |  |
| Basic surface material:Ceramic                                       |  |  |  |
| Color of surface:Black   |  |  |  |
| Length electrical supply cord:110.0 cm                               |  |  |  |
| Sealed Burners:  |  |  |  |
| heating with booster: Rear left                                      |  |  |  |
| Power of 2nd heating element (kW):2.2 kW                             |  |  |  |
| Power of 5th heating element (kW): 1.4 kW                            |  |  |  |
| Connection rating:   |  |  |  |
| Voltage:   |  |  |  |
| Frequency: 50; 60 Hz   |  |  |  |
| Energy input:Electric  |  |  |  |
| Plug type:no plug  |  |  |  |
| Appliance Dimensions (h x w x d) (in): x x                           |  |  |  |
| Dimensions of the packed product: 4.96 x 23.74 x 29.64               |  |  |  |
| Net weight:  |  |  |  |
| Gross weight:  |  |  |  |
| Total number of positions that can be used at the same time: 3       |  |  |  |
| Length electrical supply cord:                                       |  |  |  |
| Required niche size for installation (HxWxD): 51 x 560-560 x 490-500 |  |  |  |
| mm   |  |  |  |
| Dimensions: 51x592x522 mm  |  |  |  |
| Dimensions of the packed product (HxWxD): 126 x 753 x 603 mm         |  |  |  |
| Net weight:  |  |  |  |
| Gross weight:  |  |  |  |
| -  |  |  |  |



### Series 2, Induction hob, 60 cm, Black, PUC61KAA5E

## The induction hob: cook fast, clean and safely while using very little energy.

- 60 cm: space for 3 pots or pans.

#### Flexibility of cooking zones

- Cooking zone rear left: 240 mm, 2.2 KW (max. power 3.1 KW)
- Cooking zone rear right: 145 mm, 1.4 KW

#### Usage convenience

- 9 stage-power: precisely adapt the heat with 9 power levels.

#### Time saving & efficiency

- PowerBoost function in the front left zone: boil water more quickly thanks to 50% more energy than at the highest standard level.
- QuickStart Function: when switching on, the hob automatically selects the cooking zone with cookware (placed in off-mode).

### Design

- frameless

#### Safety


- Childproof lock: prevent unintended activation of the hob.
- Main on/off switch: switch off all cooking zones at the touch of a button.
- Safety switch-off: for safety reasons, heating stops after a preset time without interaction (customizable).

#### Installation

- Dimensions of the product (HxWxD mm): 51 x 592 x 522
- Required niche size for installation (HxWxD mm) :  $51 \times 560 \times (490 500)$
- Min. worktop thickness: 16 mm
- Connected load: 4.6 KW
- PowerManagement Function: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord: 1.1 m, connected directly



## Series 2, Induction hob, 60 cm, Black, **PUC61KAA5E**



measurements in mm 51 (B) ≥ 16 (**C**) ≥ 40 (A)


- A: Minimum distance from the hob cut-out to the wall.
   B: Recessed depth
   C: The clearance between the surface of the worktop and the top of the front of the oven must be 30 mm. See space requirements for the oven.


The worktop into which the hob is installed must withstand loads of approx. 60 kg; suitable substructures must be used if required.

| D       | E    | F    |
|---------|------|------|
| 585-600 | 50   | ≥ 35 |
| > 600   | > 50 | > 50 |

① Ventilation gap must be present

All measurements in mm





Measurements in mm