



Color Variants

BOP250612
Glass front in Gaggenau Metallic
Width 24" (60 cm)

Included accessories

- x enamel baking tray.
suit. pyrolytic clean.
- x grill shelf.
- x grill tub with grid.
- x pluggable meat probe.

Optional accessories

- BA016165
- Pull-out system
- BA026115
- Baking tray, enameled
- BA036165
- Wire rack, chromium-plated
- BA056115
- Heating element for baking stone and cast-iron roaster
- BA056133
- Baking stone
- BA226105
- Broil pan, enameled
- BS020002
- Pizza peel, additional set of 2
- GN340230
- Non-stick aluminum cast-iron roaster

Product Variants

BOP251612
200 series single oven
Glass front in Gaggenau Metallic
Width 24" (60 cm)
left-hinged

BOP250612
200 series single oven
Glass front in Gaggenau Metallic
Width 24" (60 cm)
right-hinged

Flush installation
Pyrolytic self-cleaning system
Universal heating system with 13 heating modes, with meat probe and baking stone operation
Automatic programs
Core temperature probe with estimation of cooking time
TFT touch display
Panel-free appliance with surface control module
Electronic temperature control from 85° F - 550° F
Net volume (76 litres)

Cooking modes

Convection. Economy convection. Top + bottom heat. Top heat. Bottom heat. Convection + bottom heat. Convection broiling. Broiling. Economy broiling. Baking stone operation. Roaster operation. Dough proofing. Defrosting.

Operation

Rotary knob and TFT touch display operation.
Clear text display in 44 languages.
Option to save 50 individual recipes (incl. core temperature probe)
Personalization of automatic programs.
Information key with use indicators.
Side-opening door opens up to 110° angle.

Features

Three-point core temperature prove with automatic shut-off and estimation of cooking time.
Automatic programs.
Baking stone outlet.
Actual temperature display.
Fast heating setting.
Timer functions: cooking time, switch-off time, short-term timer, stopwatch.
60 W halogen light on the top.
Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.
Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety shut-off.
Cooled housing with temperature protection.

Cleaning

Pyrolytic self-cleaning.
Gaggenau Clean-Enamel.
Heated air cleaning catalyst.

Planning notes

Door hinge not reversible.
The door panel front of the appliance extends 13/16" from the cabinet front.
The outer edge of the door handle extends 2 13/16" from the cabinet front.
Necessary lateral gap between appliance door and cabinet front of min. 3/16".
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

Product Features
Cooking mode
Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air broiling, Hot Air-Eco, Roasting function, Top heat
Integrated Cleaning system
Self Clean
Interior Lights - primary cavity
1
Pull-out system
Accessory
Timer settings
Alarm, Off, On, timer
x enamel baking tray,suit. pyrolytic clean, x grill shelf, x grill tub with grid, x pluggable meat probe
Bake Element Wattages primary cavity (W)
1300
Broil Element Wattages primary cavity (W)
3000
Convection Element Wattages primary cavity (W)
2100
Microwave Wattages (W)
Drawer wattage (W)

Consumption and connection features
UPC code
825225957430
Product color
Alternative colors available
Energy source
Electric
Watts (W)
4030
Current (A)
17
Volts (V)
208/220-240
Frequency (Hz)
60
Approval certificates
CSA, ETL, UL
Power Cord Length
39 3/8
Plug type
fixed connection
23 1/4" x 22 1/16" x 21 11/16"
Product packaging dimensions (HxWxD) (in)
30 11/16" x 26 3/4" x 29 15/16"
Net weight (lbs)
125.000
Gross weight (lbs)
134.000
2020-09-14
Page 1

When planning a corner solution, pay attention to the 110° door opening angle.
For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 9/16". The planning notes for the cooktops (particularly regarding ventilation, gas/ electric connection) must be taken into account.
To achieve the 21 5/8" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.
Plan a power outlet outside of the cut-out niche.
The LAN port can be found at the back on the upper right side.

Rating

Total rating 4.0 KW.
Total Amps: 17 A.
208 / 220 - 240 V / 60 Hz.
Connection cable 47 1/4" without plug.
Plan for a LAN cable.
Power consumption standby/display off 0.5 W.
Power consumption standby/network 1.4 W.
Time auto-standby/network 20 min.
Please check the user manual for how to switch off the WiFi module.

