



Product Features

Innovation

Side opening door for easy access to oven cavity

Fast preheat (around 7 minutes)

Fast 2-hour self-clean mode

Multi-point meat probe for better precision when cooking poultry

Performance

Full Access® telescopic rack holds up to 45 pounds, integrated easy grip handle

Halogen lighting illuminates the oven cavity

16 cooking modes

Max broil element with 4800 watts

Design

Specially crafted gray glass on stainless steel for a luxurious look and finish

Designed for flexibility -- standard or flush installation into kitchen cabinets

Notes: Please refer to installation instructions. Installation instructions are available at www.thermador.com. Specifications are correct at the time of printing. Thermador reserves the right to change product specifications and design at any time, without notice.

1 800 735 4328 | WWW.THERMADOR.COM | 1901 Main Street, Suite 600 Irvine, CA 92614

©2019 BSH HOME APPLIANCES CORPORATION, ALL RIGHTS RESERVED LITHO DATE: 03/2019

Combination Oven with Microwave or Speed Oven, flush mount installation Top View Bottom Hinge Door

(19 mm)

(25 mm) → 28¹/2" (724 mm) → 30" (762 mm) →

Souble or combo oven sut-out beight

Side View-Co

3/4"

(19 mm)

measurements in inches (mm)

 Well oven junction box may be located above or to the right or left of the unit within neach of the power cable.



Product Features

Cooking mode	3rd element convection, Convection Bake.
	Convection Broil,
	Convection Roast.
	Conventional heat.
	Dehydrate, Dough
	proving setting, Full width
	broil, Half width variable
	broil, Hot air broiling,
	Intensive hot air, low
	temperature cooking,
	Pizza setting, Rotisserie,
	Top heating, 1/3
	bottom heat., warming
Cooking method secondary cavity	3rd element convection,
	Convection Broil,
	Defrosting, Hot air
	grill, Intensive hot air,
	Microwave, Pizza
	setting, Warming
Integrated Cleaning system	Self Clean
Number of interior lights	2
Timer	Yes
Included accessories	1 x rotary spit, 1 x
	Broiler pan, 1 x grid
	high, 1 x grid flat, 3 x
	telescopic rack, 1 x
	temperature probe /lower
Bake Element Wattages primary cavity (W)	0
Broil Element Wattages primary cavity (W)	4800
Convection Element Wattages primary cavity	2000
(W)	

Technical Specification

UPC code	825225936947
Product color	Stainless steel
Energy source	Electric
Watts (W)	10200
Current (A)	16
Volts (V)	240/208
Frequency (Hz)	60
Approval certificates	CSA
Power Cord Length	60"
Plug type	fixed connection, no plug
Required cutout size (HxWxD) (in)	49 1/2" x 28 1/2" x 24"
Overall appliance dimensions (HxWxD) (in)	49" x 29 3/4" x 23 7/8"
Product packaging dimensions (HxWxD) (in)	55 1/8" x 31 1/2" x 34"
Net weight (lbs)	287
Gross weight (lbs)	

Notes: Please refer to installation instructions. Installation instructions are available at www.thermador.com.specifications are correct at the time of printing. Thermador reserves the right to change product specifications and design at any time, without notice.

1 800 735 4328 | WWW.THERMADOR.COM | 1901 Main Street, Suite 600 Irvine, CA 92614

©2019 BSH HOME APPLIANCES CORPORATION, ALL RIGHTS RESERVED LITHO DATE: 03/2019