### 36-Inch Pro Harmony® Standard Depth Dual Fuel Range





# **Product Features**

#### Innovation

The perfect blend of professional grade cooking with a New Contemporary Design that will fit seamlessly into any Kitchen style with a color TFT interface for a full range of cooking functions

Exclusive, patented Star® Burner – most even heating, unsurpassed flame coverage

Convection Bake offers precise multi-level baking results

Precision simmering capabilities as low as 100°F (375 BTU) with 2 ExtraLow® Simmer burners

Superfast 2-hour self-clean mode - fastest in the industry

### **Performance**

ExtraLow® feature provides a wide range of temperature control, perfect for simmering delicate sauces

Electronic re-ignition will automatically re-ignite the burner in case the flame goes out

Every front burner provides 18,000 BTUs for added convenience

Three Full Access® telescopic rack holds up to 45 pounds, integrated easy grip handle

Powerful, 2,750 watt convection bake and 4,000 watt broil elements

### Design

Truly Flush Mounted™, 24" standard cabinet depth

Patented Pedestal Star® Burner with QuickClean Base™


Powerful halogen lighting illuminates the oven cavity


Restaurant style metal knobs

Large oven door window for maximum viewing

Notes: Please refer to installation instructions. Installation instructions are available at www.thermador.com. Specifications are correct at the time of printing. Thermador reserves the right to change product specifications and design at any time, without notice.







# **Product Features**

Total number of cooktop burners	6
Cooking mode	3rd element convection,
	Centre-area grill/
	broiler, Convection
	Bake, Convection Broil,
	Conventional heat,
	Roasting function,
	Selfcleaning pyrolitic
Integrated Cleaning system	Self Clean
Oven Control	Electronic
Knob Material	Full metal
Included accessories	1 x Broiler pan,
	1 x island trim
Sealed Burners	Yes
Number of Double grates	3
Bake Element Wattages primary cavity	2000
Convection Element Wattages primary	2750
cavity	
Number of gas burners	6
Location of 1st heating element	front left
Power of 1st burner	18000
Location of 2nd heating element	center left
Location of 3rd heating element	back left
Power of 3rd burner (BTU)	15000
Location of 4th heating element	middle back
Power of 4th burner (BTU)	15000
Location of 5th heating element	back right
Power of 5th burner	15000
Location of 6th heating element	center right
Safety device	automatic reignition,
•	Electronic flame
	control, Overheating
	protection, Thermostat

# **Technical Specification**

•	
UPC code	825225925194
Alternative gas type	Liquid gas 27,5
	mbar (USA)
Total BTU load	99000
Watts	6400
Fuse protection	30
Volts	240/208
Frequency	60
Approval certificates	CSA
	36" width slide-in
Overall appliance dimensions (HxWxD) (in)	35 7/8" x 35
	15/16" x 24 3/4"
Variable cooker height (in)	1"
AHAM usable cavity size	3
Due do et ma else sinos discome in ma (11/4/4/2D)	40 4/4 40 4/0 40 0/0