

**Series 4, island cooker hood, 90 cm,
Stainless steel
DIB97IM50**



DHZ1256 Chimney extension 1600 mm, DHZ5346 Standard odor filter (replacement), DHZ5385 Standard recirculation kit, DIZ2CB114 Clean Air Standard recirculation kit, DIZ2CX5C6 Clean Air Plus recirc. kit external, DIZ2FX5D1 Long Life recirculation kit external, DZZ0XX0P0 Long Life odor filter (replacement), DZZ1XX1B6 Clean Air Plus odor filter (replacement), DHZ1231 Adapter for roof inclination left/right, DHZ1241 Adapter for roof inclination front/back, DHZ1246 Chimney extension 1100 mm, DHZ1251 Extension for mounting kit 500 mm, DHZ1253 Extension for mounting kit 1000 mm, DZZ2CB1B4 Clean Air Standard odor filter (repl.), HEZG9AS00S Adapter

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **Especially silent:** maximal extractor performance with minimal noise
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **TouchSelect control:** quick touch-control selection of desired settings and light.

Typology:	Island/Ceiling
Length electrical supply cord:	130.0 cm
Height of the chimney:	691-871/691-991 mm
Height of product, without chimney:	53 mm
Net weight:	29.2 kg
Type of control:	Electronic
Number of speed settings:	3-stages + intensive setting
Max. air extraction:	438 m ³ /h
Boost position output recirculating:	527 m ³ /h
Max. air recirculation:	390 m ³ /h
Boost position air extraction:	754 m ³ /h
Number of lights:	4
Noise level:	57 dB(A) re 1 pW
Diameter of air outlet:	150 / 120 mm
Grease filter material:	Washable aluminium
Odour filter:	No
Optional accessories:	DHZ1256, DHZ5346, DHZ5385, DIZ2CB114, DIZ2CX5C6, DIZ2FX5D1, DZZ0XX0P0, DZZ1XX1B6, DHZ1231, DHZ1241, DHZ1246, DHZ1251, DHZ1253, DZZ2CB1B4, HEZG9AS00S
Type of lamps used:	LED
Grease filter type:	Kassette
Connection rating:	256 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	60; 50 Hz
Plug type:	Gardy plug w/ earthing
Installation typology:	Island
Material body:	Stainless steel
Plug type:	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in):	x x
Dimensions of the packed product:	33.07 x 24.01 x 40.94
Net weight:	64.000 lbs
Gross weight:	88.000 lbs
Motor location:	Integrated motor in hood chimney
No-return airflow flap:	Yes
Length electrical supply cord:	130.0 cm
Dimensions of the product, with chimney (if exists):	744-1044 x 898.0 x 600.0 mm
Dimensions of the packed product (HxWxD):	... 840 x 610 x 1040 mm
Net weight:	29.2 kg
Gross weight:	39.7 kg



Series 4, island cooker hood, 90 cm, Stainless steel DIB97IM50

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

Design:

- Island chimney hood
- Appliance colour: brushed steel
- Ceiling mounted hood

Environment and safety:

- Energy Efficiency Class: B*
- Average Energy Consumption: 74.3 kWh/year*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Noise min./max. Normal Level: 45/57 dB*

Comfort:

- TouchControl for extractor speeds and light
- Electronic controls
- TouchControl with Electronic display
- 3 speeds plus intensive setting via TouchControl
- Electronic controls via TouchControl with Electronic display
- TouchControl (3 speeds plus intensive setting) with Electronic display
- easy to clean Innerframe
- Metal grease filter, dishwasher safe

Operating and power:

- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Max. extraction rate: 754 m³/h

Power:

- Power rating: 256 W
- Twin channel high performance fan motor
- Capacitor energy efficient
- Light Intensity: 409 lux

Measures:

- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Suitable for ducted or re-circulated extraction

Technical information:

- 4 x 1,5W LED
- Colour Temperature: 3500 K
- with one-way flap
- Extraction rate according to EN 61591 Ø 15 cm:
 - max. Normal use 438 m³/h
 - Intensive 754 m³/h
- Extraction rate exhaust air according to EN 61591 max. 438 m³/h
- Maximum extraction rate exhaust air 438 m³/h according to EN

61591

- Extraction rate exhaust air according to EN 61591:
 - max. normal use 438 m³/h, intensive 754 m³/h
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 57 dB(A) re 1 pW (44 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
 - Max. normal use: 57 dB(A) re 1 pW (44 dB(A) re 20 µPa sound pressure)
 - Intensive: 68 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014

**Series 4, island cooker hood, 90 cm,
Stainless steel
DIB97IM50**

